

State of New Mexico
Energy, Minerals and Natural Resources

RECEIVED

SEP 17 2010

HOBBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-041-20754

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

NMNMM 01456685

7. Lease Name or Unit Agreement Name

Horton Federal

8. Well Number

36

9. OGRID Number

257420

10. Pool name or Wildcat

Milnesand (San Andres)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

EOR Operating Company

3. Address of Operator

200 N. Loraine, Suite 1440. Midland, TX 79701

4. Well Location

Unit Letter B : 900 feet from the North line and 1581 feet from the East line
Section 30 Township 8S Range 35E NMPM County Roosevelt

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4211.9 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐P AND A ☐CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Start date: 9/13/10. Completion date 9/15/10.

Reactivate well as part of the NMOCD-ACO-265-A.

Repair, down hole equipment failure (rods, pump and or tbg) and return well to production.

1. RU. TOH w/ rods & pump. Pump was stuck in SN.

2. Released 2 7/8" x 5 1/2" TAC tagged TD. 1' of fill. TOH w/ 2 7/8" tbg. Replaced TAC & SN.

3. TIH w/ 2 7/8" tbg. Set TAC w/ 14 pts. ND BOP's. NU wellhead.

4. TIH w/ new 1 3/4" x 16' insert pump & existing rods. Spaced out. Tested pump action. Hung well off. NU wellhead.

5. RD released rig.

(2 7/8" tbg. @ 4722'. SN @ 4718'. 5 1/2", 15.5# csg @ 4806'. Perforations 4655'-4688' & 4712'-4732')

Start Date:

09/13/2010

Rig Release Date:

09/15/2010

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Well Operations Supervisor

DATE 09/16/10

Type or print name L.A. Spittler, Jr.

E-mail address: lspittler@enhancedoilres.com

PHONE: 432-688-0303

For State Use Only

APPROVED BY:

TITLE

PETROLEUM ENGINEER

DATE

SEP 21 2010

Conditions of Approval (if any):

pm