* *		
Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
Office	D AC 1 131 (D)	14. 27. 2004
District I	Energy, Minerals and Natural Resource OIL CONSERVATION DIVISION 1220 South St. Francis Dr.	WELL API NO.
District II		30-025-11750
1301 W Grand Ave., Artesia, NM 88210	* Off CONSERVATION DIVISION	5. Indicate Type of Lease
District III OCT 1 2 20	1220 South St. Francis Dr.	STATE FEE
1000 Rio Brazos Rd., Aztec, NMQ 10 1 2 20 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St Francis Dr., Santa fel 01373650	CD Summer C, 1447 07303	I I
	S AND REPORTS ON WELLS	NMJ - 540 7. Lease Name or Unit Agreement Name:
	S TO DRILL OR TO DEEPEN OR PLUG BACK TO A	South Justis Unit "E"
DIFFERENT RESERVOIR. USE "APPLICATION OF THE PROPERTY OF THE P		South Justis Unit "E"
PROPOSALS.)	•	
1. Type of Well: Oil Well ⊠ Gas	Well Other	8. Well No. 19
2. Name of Operator		9. OGRID Number
Legacy Reserves Operating I	LP	240974
3. Address of Operator		10. Pool name or Wildcat
PO Box 10848, Midland, TX	79702	Justis-Blinebry-Tubb-Drinkard
4. Well Location		
Unit Letter <u>D</u> : <u>66</u>	The state of the s	
Section 24	Township 25-S Range 37-E	NMPM County Lea /
	. Elevation (Show whether DR, RKB, RT, GR,	
	3099' KB	10 A Mars 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Pit or Below-grade Tank Application	or Closure	
Pit type Depth to Groundwate	er Distance from nearest fresh water well	Distance from nearest surface water
Pit Liner Thickness: mil		bbls; Construction Material
12 Check Anni	ropriate Box to Indicate Nature of Not	
12. Check rippi		ice, report or other Data
NOTICE OF INTE	ENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PL		VORK ☐ ALTERING CASING ☐
_		DRILLING OPNS. D P AND A
PULL OR ALTER CASING MI	ULTIPLE 🗌 CASING/CEI	
0/	OMPLETION	
C	OWN ELTION	
OTHER:	☐ OTHER:	
OTHER: 13. Describe proposed or completed op	OTHER: Derations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date of
OTHER: 13. Describe proposed or completed opstarting any proposed work). SEE	OTHER: Derations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date of ach wellbore diagram of proposed completion or
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion.	OTHER: perations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Atta	ach wellbore diagram of proposed completion or
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed	OTHER: perations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Atta quipment. Dig out cellar. NU flange and BO	ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN.
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstring.	OTHER: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaining and BO and tag plug @ 5000'. Circulate hole with	P. Start RIH w/ tbg. SDFN. h mud laden fluid. Spot 40 sx class C cement @
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing econo/22/10 Finish picking up workstring 5000'. Pull out of cement. WOC. Tags	OTHER: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaining and BO and tag plug @ 5000'. Circulate hole with	ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN.
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Taggpacker and 1000' tbg. SDFN.	OTHER: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Atta quipment. Dig out cellar. NU flange and BC ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg	PP. Start RIH w/ tbg. SDFN. mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/
OTHER: 13. Describe proposed or completed opstarting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31	OTHER: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Atta quipment. Dig out cellar. NU flange and BO ng and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement.	och wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/
OTHER: 13. Describe proposed or completed opstarting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and So	OTHER: perations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Atta quipment. Dig out cellar. NU flange and BO ng and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. gz'd 40 sx class C cement. WOC. NO TAG.	ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight.
OTHER: 13. Describe proposed or completed opstarting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagp packer and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6	ornations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. r	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location.
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	ornations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld of	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagp packer and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6	ornations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. r noe. dug out cellar. Cut off wellhead. Weld ced off.	ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. r toe. dug out cellar. Cut off wellhead. Weld ced off.	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. roe. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging traditional statement of the statemen	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at which may be found at	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. roe. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging traditional statement of the statemen	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sc 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 610/05/10 Moved in welder and backh	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at which may be found at	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and So 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6 10/05/10 Moved in welder and backh dead men and cleaned location. Move	other: orations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BC and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. r toe. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.sta	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd.
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tag: packer and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sq. 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg. @ 610/05/10 Moved in welder and backh dead men and cleaned location. Move	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.sta	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off of well bore only. Tretained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tag: packer and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sq. 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg. @ 610/05/10 Moved in welder and backh dead men and cleaned location. Move	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement. yz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.sta	ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off of well bore only. Tetained pending receipt Report of Well Plugging) OCD Web Page under te.nm.uslocd.
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6 10/05/10 Moved in welder and backh dead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen seen seen seen seen seen seen se	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.states true and complete to the best of my knowledge arding to MOCD guidelines, a general permit [Ach wellbore diagram of proposed completion or SP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ IN WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off Ori well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tag: packer and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sq. 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg. @ 610/05/10 Moved in welder and backh dead men and cleaned location. Move	orher: oerations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.states true and complete to the best of my knowledge arding to MOCD guidelines, a general permit [ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ I. WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off of well bore only. Tretained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrint 5000'. Pull out of cement. WOC. Taggacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 60 10/05/10 Moved in welder and backhed dead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen will be constructed	orher: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BC ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.state ding to NMOCD guidelines, a general permit [Ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ IN WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off Of well bore only. Tretained pending receipt Report of Well Plugging) OCD Web Page under tee.nm.usiocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan In Superintendent DATE 10/08/10
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6 10/05/10 Moved in welder and backhedead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen will be constructed or c	orher: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BC ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.state ding to NMOCD guidelines, a general permit [Ach wellbore diagram of proposed completion or SP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ IN WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off Ori well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrint 5000'. Pull out of cement. WOC. Taggacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 60 10/05/10 Moved in welder and backhed dead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen will be constructed	orher: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BC ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.state ding to NMOCD guidelines, a general permit [Ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ IN WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off Of well bore only. Tretained pending receipt Report of Well Plugging) OCD Web Page under tee.nm.usiocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan In Superintendent DATE 10/08/10
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrint 5000'. Pull out of cement. WOC. Taggacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 60 10/05/10 Moved in welder and backhed dead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen/will be constructed or closed according to the seen of the seen	orher: orations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BO ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 60'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld cell off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.state of the complete to the best of my knowledge are ding to NMOCD guidelines \(\begin{array}{cccccccccccccccccccccccccccccccccccc	ach wellbore diagram of proposed completion or OP. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. On Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan Telephone No. 432-689-5200
OTHER: 13. Describe proposed or completed or starting any proposed work). SEE recompletion. 09/21/10 MIRU rig and cementing ed 09/22/10 Finish picking up workstrin 5000'. Pull out of cement. WOC. Tagpacker and 1000' tbg. SDFN. 09/23/10 Finish running in hole to 31 Perf'd csg. @ 2000'. Set paker and Sci 09/24/10 Tagged plug @ 1705'. POH @ 384'. Lay down tbg. Perf'd csg @ 6 10/05/10 Moved in welder and backhedead men and cleaned location. Moved in the seen/will be constructed or closed according to the seen will be constructed or c	orher: Derations. (Clearly state all pertinent details, a RULE 1103. For Multiple Completions: Attaquipment. Dig out cellar. NU flange and BC ag and tag plug @ 5000'. Circulate hole with ged plug @ 4515'. Stand back 3450' of tbg 00'. Set packer. Sqz'd 50 sx class C cement qz'd 40 sx class C cement. WOC. NO TAG. to 220'. Perf'd csg. @ 577'. Set packer and 50'. Sqz'd 20 sx class C cement to surface. race. dug out cellar. Cut off wellhead. Weld ced off. Approved for plugging Liability under bond is of C-103 (Subsequent which may be found at Forms, www.cmnrd.state ding to NMOCD guidelines, a general permit [ach wellbore diagram of proposed completion or P. Start RIH w/ tbg. SDFN. In mud laden fluid. Spot 40 sx class C cement @ and lay down rest. Perf'd csg. @ 3450'. RIH w/ WOC. Tagged plug @ 3280'. POH to 1600'. Re-Sqz'd 50 sx cement. WOC overnight. Sqz'd 50 sx class C cement. WOC. Tagged plug igged down cleaned location. In Dty Hole Marker. Backfilled cellar. cut off of well bore only. retained pending receipt Report of Well Plugging) OCD Web Page under te.nm.us/ocd. In d belief. I further certify that any pit or below-grade tank or an (attached) alternative OCD-approved plan . Telephone No. 432-689-5200