

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

October 13, 2009

RECEIVED

OCT 12 2010

HOBBSOCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-025-36713

5. Indicate Type of Lease

STATE ☒ FEE ☐ ☒

6. State Oil & Gas Lease No.

VO-6057

7. Lease Name or Unit Agreement Name

Dolly BER State Com

8. Well Number

1

9. OGRID Number

025575

10. Pool name or Wildcat

Undes. Sand Springs; Atoka-Morrow

Sand Springs; Mississippian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)1. Type of Well: Oil Well ☐ Gas Well ☒ Other P&A

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter M : 660 feet from the South line and 660 feet from the West line
Section 34 Township 10S Range 34E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4201'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/22/10 - NU BOP.

9/23/10 - Pumped 123 bbls down tubing, broke circulation up 5-1/2" casing.

9/24/10 - Pumped 80 bbls fresh water. Broke circulation. Pumped 75 sx Class "H" cement at 12,308'. TOC at 11,627'. WOC 4 hrs.

Tagged cement plug at 11,771'. Pumped 25 sx Class "H" cement with 226' fill at 11,455'. Est TOC at 11,229'.

9/27/10 - Tagged cement plug at 11,217'. Pumped 25 sx Class "H" cement at 8514'. Est TOC at 8288'. Did not have to tag. Pumped 25

sx Class "C" cement at 5612'. Est TOC at 5358'. Did not have to tag. Pumped 25 sx Class "C" cement at 4988'. Est TOC at 4734'.

Did not have to tag. Pumped 25 sx Class "C" cement at 4301'. Est TOC at 4047'.

9/28/10 - Tagged cement plug at 4074'. Pumped 25 sx Class "C" cement at 2014'. Est TOC at 1760'. Did not have to tag. Perforated 4

holes at 483'. Broke circulation up 5-1/2" x 9-5/8". Pumped 150 sx Class "C" cement to surface. ND BOP. Topped well off.

10/1/10 - Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar back in, dug out anchors. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.wemind.state.nm.us/ocd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE October 5, 2010Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Staff MGR DATE 10-14-10

Conditions of Approval (if any):