

State of New Mexico
Energy, Minerals and Natural Resources

RECEIVED

OCT 12 2010

HOBBSOCD

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. 30-025-38190
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-6266
7. Lease Name or Unit Agreement Name Rebecca BJB State Com
8. Well Number 2
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat; Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☒2. Name of Operator
Yates Petroleum Corporation3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter P : 800 feet from the South line and 990 feet from the East line
Section 18 Township 12S Range 32E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4392'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/28/10 – NU BOP.

9/29/10 – Pumped 25 bbls and broke circulation. Pumped 25 sx Class "H" cement at 8565'. WOC 3 hrs. Pumped 180 bbls mud gel. Tagged cement plug at 8514'. Called Maxey Brown with NMOCD-Hobbs and he approved to move to next plug. Pumped 25 sx Class "C" cement at 6514'. Est TOC at 6260'. Did not have to tag. Pumped 25 sx Class "C" cement at 3803'. Est TOC at 3549'.

9/30/10 – Tagged cement plug at 3589'. Tested casing to 500 psi, held good. Perforated 4 holes at 1455'. Loaded up and pressure tested casing to 500 psi, could not pump into perms. Pumped 25 sx Class "C" cement at 1521'. WOC 2 hrs. Tagged cement plug at 1277'. Perforated 4 holes at 478'. Broke circulation up 5-1/2" x 8-5/8". Pumped 125 sx Class "C" cement to surface. ND BOP. Topped well off.

10/1/10 – Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar back in and dug up anchors and cleaned location.

WELL IS PLUGGED AND ABANDONED.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.cmnr.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE October 5, 2010Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168**For State Use Only**APPROVED BY: [Signature] TITLE STAFF MGR DATE 10-14-10

Conditions of Approval (if any):