

State of New Mexico  
Energy, Minerals and Natural Resources

RECEIVED

OCT 14 2010

HOBBSOCD

## OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. / 30-025-34898
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. V-1315
7. Lease Name or Unit Agreement Name East Sand Springs BFZ State /
8. Well Number 3
9. OGRID Number 025575
10. Pool name or Wildcat Sand Springs; Abo (Oil) /

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A ☒

2. Name of Operator

Yates Petroleum Corporation /

3. Address of Operator

105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter N : 1000 feet from the South line and 1400 feet from the West line  
Section 6 Township 11S Range 35E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4182'GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/1/10 – NU BOP. Pumped 250 bbls mud gel. Pumped 35 sx Class “H” cement at 9217’.

10/4/10 – Tagged cement plug at 8942’. Pumped 25 sx Class “C” cement at 6311’. Est TOC at 6057’. Did not have to tag. Perforated 4 holes at 4192’. Broke circulation up 5-1/2” x 8-5/8”. Pumped total of 75 bbls mud. Pumped 45 sx Class “C” cement at 3600’. Displaced cement down to 3992’. WOC 1 hr. Tagged cement plug at 3970’. Perforated 4 holes at 2150’ and pumped 45 sx Class “C” cement. Displaced cement down to 1950’.

10/5/10 – Tagged cement plug at 1914’. Perforated 4 holes at 437’. Circulated 110 sx Class “C” cement up 5-1/2” x 8-5/8” casing to surface. Cleaned location.

10/9/10 – Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar back in and dug out anchors. **WELL IS**

**PLUGGED AND ABANDONED.**

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, [www.cmnr.state.nm.us/oed](http://www.cmnr.state.nm.us/oed).

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE October 13, 2010Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168**For State Use Only**APPROVED BY: [Signature] TITLE STAFF MGR DATE 10-18-10

Conditions of Approval (if any):