RECEIVED	
Submit 1 Copy To Appropriate District State of New Mexico	Form C-103
Office District 1 NOV 0 Energy, Minerals and Natural Resources	October 13, 2009
1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avc., Artesia, NM 88210 BBSOIC CONSERVATION DIVISION	WELL API NO. 3000520828
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fc, NM 87505	LG 2464
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Loveless LQ State
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other SWD	8. Well Number #5
2. Name of Operator Nordstrand Engineering	9. OGRID Number 230757
3. Address of Operator	10. Pool name or Wildcat \(\sullet \)
3229 D'Amico Suite 200, Houston Texas 77019	Tomahawk San Andres
4. Well Location	
Unit Letter D : 990 feet from the North line and	990feet from theWestline
Section 36 Township 7S Range 31E	NMPM Chaves County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GL Elevation 4424	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT	ГЈОВ 🔲
DOWNHOLE COMMINGLE	
OTHER: OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated dates	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
10/1/10 Install BOP. RIH with tubing and spot 40 sx class c cement at 4170'. Shut in over weekend.	
10/4/10 RIH and tag cement at 3841'. POH with tubing and rig up wireline. Perf casing at 2210', 1775', and 80'.	
RIH with packer and tubing. Squeezed perfs at 2210 with 45 sx class cement. Bottom salt plug. 10/5/10 RIH and tag cement at 2080.79'.	
10/6/10 POH to 1100', set packer, and squeezed perfs at 1775' with 130 sx class c cement. 8 5/8 casing shoe and top of salt plug.	
WOC and tag cement at 1330'. Too low. Spotted additional 10 sx class c at 1330. Shut in over night.	
10/7/10 Tagged plug at 1180'. Lay down remaining tubing. Rig up on 4 1/2 casing. Pumped class c cement down 4 1/2 casing to perfs at 80' and up 4 1/2 x 8 5/8 annulus to surface. Pumped approx. 22 sx.	
10/8/10 Cut off wellhead, install marker plate, and cut off anchors.	
	-
Approved for plugging of well bore only. Liability under bond is retained pending receipt	
of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under	
Forms, www.emnrd.state.nm.us/ocd.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE TITLE Field Representative DATE 10/26/2010	
Type or print name Thomas E. Nordstrand E-mail address: tom@nmbvi.com PHONE: 505-321-7671	
For State Use Only	
APPROVED BY: Jongalie TITLE STAFF MAR DATE 11-3-10	
Conditions of Approval Lift any):	DATE 1/-3-10