

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Amended

Form C-103
Revised June 10, 2003

WELL API NO.
30-025-36433

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Shelley 36 State

8. Well Number
003

9. OGRID Number
023230

10. Pool name or Wildcat
Skaggs; Drinkard (57000)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Tom Brown, Inc.

3. Address of Operator
P O Box 2608, Midland, TX 79702

4. Well Location

Unit Letter L : 2200 feet from the South line and 790 feet from the West line

Section 36 Township 19S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3596 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐


CASING TEST AND CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/28/2003 Ran 169 jts of 5-1/2" 17#, L-80 csg (Total length 7229.94 set @ 7225') Cement first stage w/ 20 bbl Super Flush + 520 sx Premium Plus 13.8 ppg, 1.69 yld. Land plug "ok" open DV tool. Circ out (did not circ cement - lift pres. = 270 psi - circ 6.5 hrs). Cement second stage w/ 20 bbl f/water + 480 sx Interfill C, 11.5 ppg, 2.728 yld. Tail in w/ 100 sx Premium Plus 14.8 ppg, 1.32 yld. Close DV tool "ok". Circ 20 sx to pit. ND BOP. Set slip

10/29/2003 Clean Pits. Release Rig @ 13:00 cst



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Diane Kuykendall TITLE Operations Asst/Tech DATE 11/18/03

Type or print name Diane Kuykendall E-mail address: dkuykendall@tombrown.com Telephone No. 432-688-9773

(This space for State use)

APPROVED BY Paul F. Kuykendall TITLE PETROLEUM ENGINEER DATE FEB 23 2004

Conditions of approval, if any: