Office	of New Mexico	Form C-103 October 13, 2009
District I  1625 N. French Dr., Hobbs, NM 8824 CF VFD	ls and Natural Resources	WELL API NO.
OIL CONSERVATION DIVISION		30-041-20942
District III  1000 Rio Brazos Rd., Aztec, NM 87410  Santa I	th St. Francis Dr.	5. Indicate Type of Lease STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410  District IV  Santa 1	Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NOBBSUCD 87505		
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		San Juan Mesa 16 State
PROPOSALS.)  1. Type of Well: Oil Well   Gas Well   Other		8. Well Number 1
2. Name of Operator		9. OGRID Number
Torch Energy Services  3. Address of Operator	, Inc.	241401 / 10. Pool name or Wildcat
1331 Lamar Ste. 1450 Ho	ougton TY 77010	Wildcat
4. Well Location	Juscon, IX //UIU	WIIdeac
Unit Letter A : 660 feet from the	e North line and 6	
Section 16 Township 4	&	NMPM Roosevelt County
11. Elevation (Show) 4613.3' G	whether DR, RKB, RT, GR, etc.)	
1019.5		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO:	SUBS	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK   PLUG AND ABANDO		
TEMPORARILY ABANDON   CHANGE PLANS	☐ COMMENCE DRIL	
PULL OR ALTER CASING ☐ MULTIPLE COMPL  DOWNHOLE COMMINGLE ☐	☐ CASING/CEMENT	JOB
_	_	
CTHED.		ompletion ra
OTHER:  13. Describe proposed or completed operations. (Clear		ompletion  give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15.	rly state all pertinent details, and	give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clear	rly state all pertinent details, and	give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15.	rly state all pertinent details, and 7.14 NMAC. For Multiple Com	give pertinent dates, including estimated date apletions: Attach wellbore diagram of
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, S	rly state all pertinent details, and 7.14 NMAC. For Multiple Com	give pertinent dates, including estimated date apletions: Attach wellbore diagram of
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, S 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  ID @ 8776.10'. Drill out	give pertinent dates, including estimated date apletions: Attach wellbore diagram of  500" OD DC's + XO + 270 jts 2.875"  t float collar + 80' cmt in shoe jt
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Start Sulfated PBT to new PBTD @ 8756.10', circ hole clear of starting any proposed work).	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3  SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, po	give pertinent dates, including estimated date apletions: Attach wellbore diagram of  500" OD DC's + XO + 270 jts 2.875"  t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtr
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Stag fill @ 8676.40' SLM, SWI, Stag fill @ 8756.10', circ hole clear to new PBTD @ 8756.10', circ hole clear Circ HCL OOH, pmp 2% KCL to displace acidizers. TOH w/drilling ass'y to	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceeds spot 500 gals 10% Accompage 7920'. SWI SDFN	give pertinent dates, including estimated date apletions: Attach wellbore diagram of  500" OD DC's + XO + 270 jts 2.875"  t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Stag fill @ 8676.40' SLM, SWI, Stag fill @ 8756.10', circ hole clear to new PBTD @ 8756.10', circ hole cle	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  FD @ 8776.10'. Drill outlean. MIRU acidizers, pr @ & spot 500 gals 10% Acc po 7920'. SWI SDFN  DC's + BS + bit. MIRU wi:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Start St	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceeds a spot 500 gals 10% Actor 7920'. SWI SDFN DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Stag fill @ 8676.40' SLM, SWI, Stag fill @ 8756.10', circ hole clear to new PBTD @ 8756.10', circ hole cle	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceeds a spot 500 gals 10% Actor 7920'. SWI SDFN DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/tbg, tag fill @ 8676.40' SLM, SWI, Start St	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceeds a spot 500 gals 10% Actor 7920'. SWI SDFN DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, SI 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT to new PBTD @ 8756.10', circ hole cleirc HCL OOH, pmp 2% KCL to displace acidizers. TOH w/ drilling ass'y to 11-22-10 NIL PSI; TOH w/ 246 jts tbg + XO + I interval w/ NIL psi, log from 8754' Perf Lower Montoya from 8712'-8728'	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceeds a spot 500 gals 10% Actor 7920'. SWI SDFN DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, SI 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT to new PBTD @ 8756.10', circ hole cleirc HCL OOH, pmp 2% KCL to displace acidizers. TOH w/ drilling ass'y to 11-22-10 NIL PSI; TOH w/ 246 jts tbg + XO + I interval w/ NIL psi, log from 8754' Perf Lower Montoya from 8712'-8728'	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3  SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, proceed & spot 500 gals 10% Accompany Accompany SWI SDFN  DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.  68 holes made. SWI SDFN	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, S 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT to new PBTD @ 8756.10', circ hole clear circ HCL OOH, pmp 2% KCL to displace acidizers. TOH w/ drilling ass'y to 11-22-10 NIL PSI; TOH w/ 246 jts tbg + XO + I interval w/ NIL psi, log from 8754' Perf Lower Montoya from 8712'-8728'  Spud Date: Rig	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  FD @ 8776.10'. Drill outlean. MIRU acidizers, proceeding to the surf of the surf of the surf of the surf. Toc 5812'.  68 holes made. SWI SDFN  g Release Date:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875"  t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf,
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, SI 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT to new PBTD @ 8756.10', circ hole cleirc HCL OOH, pmp 2% KCL to displace acidizers. TOH w/ drilling ass'y to 11-22-10 NIL PSI; TOH w/ 246 jts tbg + XO + I interval w/ NIL psi, log from 8754' Perf Lower Montoya from 8712'-8728'	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  FD @ 8776.10'. Drill outlean. MIRU acidizers, proceeding to the surf of the surf of the surf of the surf. Toc 5812'.  68 holes made. SWI SDFN  g Release Date:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875"  t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf,
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH W/ tbg, tag fill @ 8676.40' SLM, SWI, SWI, SWI, SWI, SWI, SWI, SWI, SWI	rly state all pertinent details, and .7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3 SDFN  FD @ 8776.10'. Drill outlean. MIRU acidizers, proceeding to the surf of the surf of the surf of the surf. Toc 5812'.  68 holes made. SWI SDFN  g Release Date:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf, and belief.
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH W/ tbg, tag fill @ 8676.40' SLM, SWI, SWI, SWI, SWI, SWI, SWI, SWI, SWI	rly state all pertinent details, and 7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3  SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, processed as spot 500 gals 10% Acco 7920'. SWI SDFN  DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.  68 holes made. SWI SDFN  g Release Date:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf, and belief.  and belief.  DATE 11/29/2010
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH w/ tbg, tag fill @ 8676.40' SLM, SWI, S 11-20-10 Rev circ hole w/ fsh wtr, tagged PBT to new PBTD @ 8756.10', circ hole clear circ HCL OOH, pmp 2% KCL to displace acidizers. TOH w/ drilling ass'y to 11-22-10 NIL PSI; TOH w/ 246 jts tbg + XO + I interval w/ NIL psi, log from 8754' Perf Lower Montoya from 8712'-8728'  Spud Date: Rig	rly state all pertinent details, and 7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3  SDFN  TD @ 8776.10'. Drill outlean. MIRU acidizers, processed as spot 500 gals 10% Acco 7920'. SWI SDFN  DC's + BS + bit. MIRU with WLM to surf, TOC 5812'.  68 holes made. SWI SDFN  g Release Date:	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf, and belief.
13. Describe proposed or completed operations. (Clear of starting any proposed work). SEE RULE 19.15. proposed completion or recompletion.  11-19-10 MIRU reverse unit, NU 5M BOP, TIH W/ tbg, tag fill @ 8676.40' SLM, SWI, SWI, SWI, SWI, SWI, SWI, SWI, SWI	rly state all pertinent details, and 7.14 NMAC. For Multiple Com  / 4.750" bit + BS + 4-3  SDFN  ID @ 8776.10'. Drill outlean. MIRU acidizers, process spot 500 gals 10% According to 7920'. SWI SDFN  DC's + BS + bit. MIRU with Will with to surf, TOC 5812'.  68 holes made. SWI SDFN  Release Date:  Regularoty Consumail address: angela@rkf	give pertinent dates, including estimated date apletions: Attach wellbore diagram of 500" OD DC's + XO + 270 jts 2.875" t float collar + 80' cmt in shoe jt mp 1000 gals 15% NEFE HCL + fsh wtretic acid from 8239' to 8756'. RDMC reline, ran CBL-GR-CCL log, repeat RIH w/ perf gun 120^ phas 4 spf, and belief.  11tant DATE 11/29/2010 ord.com PHONE: 432-682-0440