Form 3160-5 (February 2005)

DEPARTMENT OF THE INTERIOR BUREAU OF LAND WAYS BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

DEC A A 2(1) Lease Serial No.

CUMPRY	IOTIOES AND DEDOOT		U D ZOIG	LC-0322233 (A)
Do not use this abandoned well.	form for proposals to d Use Form 3160-3 (APD)	rill or to re-enteral for such proposal	BSOCAL Indian, Allottee of s.	or Tribe Name
SUBMI	T IN TRIPLICATE – Other inst	ructions on page 2	7. If Unit of CA/Agre	ement, Name and/or No.
1. Type of Well	THE THE LIGHTE - GUICI WISH	actions on page 2.		
☑ Oil Well ☐ Gas V	8. Well Name and No	Hobbs G/SA Unit 443		
Name of Operator Occidental F	Permian LTD		9. API Well No	80-025-28958
3a. Address ATTN: Mark Stephens PO Box 4294, Houston, TX 77210-4294 3b. Phone No. (include area code) 432-685-5640			de) 10. Field and Pool or	
4. Location of Well (Footage, Sec., T.R., M., or Survey Description)			11. Country or Parish,	
1300' FSL and 160' FEL SESE(P) Section 30 T18S R38E				Lea, NM
12. CHEC	CK THE APPROPRIATE BOX(E	S) TO INDICATE NATURI	OF NOTICE, REPORT OR OTH	ÉR DATA
TYPE OF SUBMISSION		TY	PE OF ACTION	
✓ Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
<u></u>	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
—	Change Plans	Plug and Abandon	Temporarily Abandon	
Final Abandonment Notice 13. Describe Proposed or Completed O	Convert to Injection	Plug Back	Water Disposal	
. CIB	r final inspection.) 4370' PBTD: 4310' P: 3920' with 35' cmt	Perfs: 4167' – 4267'		completed and the operator has
	8", 32# & 24#, K-55 @ 1513' w ", 14#, K-55 @ 4370' with 700 :			
2. C 3. S 4. S 5. S 6. P V	RIH and tag existing CIBP with of Circulate 10# MLF. Spot 30 sx cmt from 3202' – 310 Spot 30 sx cmt from 2705' – 260 Spot 48 sx cmt from 1640' – 144 Serforate @ 400'. Squeeze and ferify. Top-off well as necessar	02'. WOC. Tag. 05'. 10'. WOC. Tag. I circulate cmt to surface.	SEE ATTACHE CONDITIONS O RECLAMATION PRO ATTACHED	OF APPROVAL
14. I hereby certify that the foregoing is to Name (<i>Printed/Typed</i>) Matthew Byrnhai	() (Title	Engineer	-
Signature /	THE STATE OF THE S	Date	1/05/10	
THE WAY	THIS SPACE FOR	R FEDERAL OR STA	TE OFFICE DIENVE	n l
Approved by Conditions of approval, if any, are attached	MAK	Title	NOV 3 0 200	DEC 0 8 2010
that the applicant holds legal or equitable t entitle the applicant to conduct operations	itle to those rights in the subject leas	e which would Office	NOV 3 0 2010 /s/ Dustin Winkle	1 1

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and will will the AND HAND HAND FIRE OFFICE.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and will the AND HAND HAND FIRE OFFICE.

CARLSBAD FIELD OFFICE (Instructions on page 2)

Occidental Permian Ltd.

NHSAU 443-30 30-025-28958 1300' FSL and 160' FEL Unit P Section 30, T18S, R38E Lea County, New Mexico

13 3/8" @ 40' with cmt to surface

8 5/8", 32# & 24#, K-55, ST&C @ 1513' with 625 sx cmt. Did not circulate. TOC @ 89'. RU 1" and cemented to surface with Class C "Neat"

Red Beds	230
Rustler 🦯	1450
Salt /	1590
Yates	2655
Seven Rivers	2856
Bowers	3300
Queen	3395
Byers	3570
Grayburg	3707
San Andres	3990

DV Tool @ 3152' with 440 sx cmt

105 jts, 5 1/2", 14#, K-55 ST&C @ 4370'
1st Stage: 260 sx cmt
2nd Stage: 440 sx cmt. Did not circulate cmt.
TOC @ 858' by CBL 01/17/1985

San Andres Open Perforations 4167' - 4183', 4191' - 4208', 4223' - 4235', 4240' - 4242', 4245' - 4247', 4257' - 4261', 4265' - 4267'

> PBTD 4310' TD 4370'

CIBP @ 3920'. Dump bailed 35' cmt on top. WOC. Tagged cmt @ 3885'.

TOF @ 4236'

Occidental Permian Ltd.

NHSAU 443-30 30-025-28958 1300' FSL and 160' FEL Unit P Section 30, T18S, R38E Lea County, New Mexico

Perforate @ 400'. Squeeze and circulate cmt to surface. Verify. Top-off well as necessary.

Spot 48 sx cmt from 1640' - 1440'. WOC. Tag.

Spot 30 sx cmt from 2705' - 2605'.

Spot 30 sx cmt from 3202' - 3102'. WOC. Tag.

Set CIBP @ 3920'. Dump bailed 35' cmt on top.

WOC. Tag.

TOF @ 4236'

PBTD 4310' TD 4370'

13 3/8" @ 40' with cmt to surface

8 5/8", 32# & 24#, K-55, ST&C @ 1513' with 625 sx cmt. Did not circulate. TOC @ 89'. RU 1" and cemented to surface with Class C "Neat"

Red Beds	230
Rustler	1450
Salt	1590
Yates	2655
Seven Rivers	2856
Bowers	3300
Queen	3395
Byers	3570
Grayburg	3707
San Andres	3990

DV Tool @ 3152' with 440 sx cmt

105 jts, 5 1/2", 14#, K-55 ST&C @ 4370'

1st Stage: 260 sx cmt

2nd Stage: 440 sx cmt. Did not circulate cmt.

TOC @ 858' by CBL 01/17/1985

San Andres Open Perforations 4167' - 4183', 4191' - 4208', 4223' - 4235', 4240' - 4242', 4245' - 4247', 4257' - 4261', 4265' - 4267' Occidental Permian LTD NMLC-0322233-A: North Hobbs G/SA Unit #443 API: 30-025-28958 Lea County, New Mexico

RE: Plugging and Abandonment Requirements, Conditions of Approval

- 1. OK (Perfs)
- 2. OK
- 3. Tag at 3072' or shallower Otherwise OK (DV Tool)
- 4. WOC and tag at 2575' or shallower Otherwise OK (Yates BOS)
- 5. Tag at 1440' or shallower Otherwise OK (TOS Casing shoe)
- 6. OK (Casing shoe Surface)
- 7. Submit a subsequent report to the BLM.

H₂S monitoring equipment shall be on location.

See attached standard COAs.

DHW 113010

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Any plug that requires a tag will have a minimum WOC time of 4 hours.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified when the wellhead is cut off to verify that cement is to surface in the casing and all annuluses.** The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

DHW 112309



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.

- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Natural Resource Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979

Tanner Nygren Natural Resource Specialist 575-234-5975

John Fast Natural Resource Specialist 575-2345996