Form 3160-5 (April 2004)

(Instructions on page 2)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007 5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

NM 04591 6. If Indian, Allottee or Tribe Name

abandoned well. Use Form 3160 - 3 (APD) for such proposals.								
SUBMIT IN TRIPLICATE- Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.				
1. Type of Well ☐ ☐ Gas Well ☐ ☐ Other ✓				8. Well Name and No.				
2. Name of Operator Devon Energy Production Company, L.P.				New Mexico 24 Federal Com 3H 9. API Well No.				
3a Address 20 North Broadway, Oklahom	3b. Phone No. (include 405-397-2584	30-025-39741 10. Field and Pool, or Exploratory Area E-K						
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Delaware /				
510 FNL & 545 FEL, Sec 24 T18S R33E				11. County or Parish, State				
,					Lea County, NM			
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, R	EPORT, OF	OTHER	R DATA		
TYPE OF SUBMISSION	YPE OF SUBMISSION TYPE OF ACTION							
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (State Reclamation Recomplete Temporarily Ab		Wel	er Shut-Off I Integrity er injectivit	y test	
Attach the Bond under which the following completion of the intesting has been completed. Find determined that the site is ready Run cement retainer to 28 950 psi (by 0.85 psi/ft fraction CaCl2 15.6 ppg. Adjust as pumping, up to 950 PSI medians.)	ectionally or recomplete horizontall he work will be performed or proviously of the operations. If the operation and Abandonment Notices shall be for final inspection.) 335 & set. RIH w/DP, sting inture gradient) or 2 bbl/min. If the per engineer pump pressure a saximum by end of job. Pull of and & clear annulus. Shut in worth work will be presented to the per engineer pump.	de the Bond No. on file versults in a multiple compfiled only after all requires to retainer, shut in anninjectivity is achieved, as cement enters DP. Eat of stinger, maintain	vith BLM/BIA. Require letion or recompletion in ments, including reclam ular, and test for inj pull out of stinger, perfore cement reache	ed subsequent in a new interval ation, have been ectivity: by ectivity: by ectivity arims maxims end of DP,	reports sha al, a Form a en complet ither the um of 40 sting into	ll be filed with 3160-4 shall be ed, and the opmaximum properties of Classoretainer, &	hin 30 days the filed once the perator has oressure of the H 2% the resume	
	n	OBRACCA FC 0 & SUM ECEINED		1 1 4	οi –	OVED 2 6 2010 Comme AND MANA D FIELD OF		
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct				1			
Title Drilling Engineer								
Signature Johnsthun (Asheral	Date	11/30/20	7 10				
	THIS SPACE FOR	FEDERAL OR S	TATE OFFICE	USE				
Approved by		<u>-</u>	HEUM ENGINE	S K	Date	DEC 0	9 2018	
Conditions of approval, if any, are certify that the applicant holds legs which would entitle the applicant t	d or equitable title to those rights i	Sandle and Sand Income	Office V					
Title 18 U.S.C. Section 1001 and Tit States any false, fictitious or fraudu	le 43 U.S.C. Section 1212, make it a lent statements or representations	a crime for any person ke as to any matter within it	nowingly and willfully s jurisdiction.	to make to an	y departme	ent or agency	of the United	