

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

RECEIVED
State of New Mexico
Energy, Minerals and Natural Resources
DEER CONSERVATION DIVISION
HOBBBS
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
October 13, 2009

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-25341
1. Type of Well: Oil Well ☐ Gas Well ☒ Other <u>Injection well</u>		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator <u>VPR operating, LLC</u>		6. State Oil & Gas Lease No.
3. Address of Operator <u>1406 Camp Craft Rd. Ste. 106, Austin, Tx 78746</u>		7. Lease Name or Unit Agreement Name <u>SFPRR</u>
4. Well Location Unit Letter <u>I</u> : <u>1980</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>East</u> line Section <u>28</u> Township <u>9S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number <u>18</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>KB 3982'</u>		9. OGRID Number <u>266091</u>
		10. Pool name or Wildcat <u>Sawyer San Andres, West</u>

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Conversion to injection ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Per Order No. 13302
8.9.10 - 8.11.10 RU JWS. PULLED & LD, RODS, PUMP & PROD. TUBING
TALLIED & PICKED UP 146 JTS OF SALTA 2 3/8" TBG W/
4 1/2" A.D. 1 NICKEL PLATED PKR. LEFT PKR SWINGING.
RU PUMP/VNC TRUCKS. DISPLACED ANNULUS W/
PKR FLUID. SET PKR AT 4853'. LOADED ANNULUS
& PRESSURED TO 550# - HELD GOOD. AD TRUCKS &
PULLING UNIT.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Agent for VPR operating, LLC DATE August 30, 2010

Type or print name M. Y. (Merch) Merchant E-mail address: mymerch@hotmail.com PHONE: (575) 492-1236
For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 12-9-10
Conditions of Approval (if any):

VPR OPERATING

EXISTING

WELL: SFPRR #18		FIELD: SAWYER			DATE: 30 NOV 2010	
LOCATION: 660' FEL & 1980' FSL		SECTION 28, T09S-R37E				
COUNTY: LEA		STATE: NEW MEXICO			BY: J R HULING	
API # 30-025-25341		SIZE, IN	WGT, # /FT	GRADE	THREAD	DEPTH
GL: 3,971'	CASING:	8-5/8	24	H-40	ST&C	430'
KB: 3,982'	CASING:	4-1/2	10.5	J-55	ST&C	5,020'
SPUD: 9/23/76	CASING:					
TD: 5,022'	PBTD: 5,028'	TUBING:	2-3/8	4.7	J-55	EUE-8RD 4853'

The diagram shows a wellbore with two main columns: an outer casing and an inner tubing. The casing is labeled '12-1/4" SURFACE HOLE DRILLED TO 430'' and '8-5/8" SURFACE CSG @ 430' CMT'd T/ Surf. W/ 300 SX CMT'. The tubing is labeled '2-3/8", 4.7#, J-55, EUE-8RD SALTA TBG W/ COATED AD-1 PACKER @ 4853''. Perforations are shown at the bottom of both columns, labeled 'SAN ANDRES PERFS: 4934' - 5004'' and 'SAN ANDRES PERFS: ORIG-9000 GAL 20% HCL ACID'. A 'TOC SURFACE' is indicated near the bottom of the casing column. A 'DV Tool ; 760 SX Cemented to Surface Thru DV Tool' is noted near the top of the casing column. The bottom of the well is labeled 'BHT = 110F'.

12-1/4" SURFACE HOLE DRILLED TO 430'
8-5/8" SURFACE CSG @ 430' CMT'd T/ Surf. W/ 300 SX CMT
DV Tool ; 760 SX Cemented to Surface Thru DV Tool
TOC SURFACE
2-3/8", 4.7#, J-55, EUE-8RD SALTA TBG W/ COATED AD-1 PACKER @ 4853'
SAN ANDRES PERFS: 4934' - 5004' *
SAN ANDRES PERFS: ORIG-9000 GAL 20% HCL ACID
4-1/2" CSG @ 5,020' CMT'd W/ 1010 SX CMT; 7-7/8" HOLE DRILLED TO 5020'; PBTD@ 5,013'

