

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BLM CARLSBAD FIELD OFFICE

Hobbs
OCD

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Occidental Permian Limited Partnership

157984

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1300 FSL 160 FEL SESE(P) Sec 30 T18S R38E

5. Lease Serial No.

LC-0322233(A)

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

8. Well Name and No.

North Hobbs G/SA 443

Unit

9. API Well No.

30-025-28958

10. Field and Pool, or Exploratory Area

Hobbs Grayburg San Andres

11. County or Parish, State

Lea

NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☒ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☒ Well Integrity

☐ Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

TD-4370' PBTD-4310' Perfs-4167-4267'

RIH & set CIBP @ 4100', dump bail 8sx cmt on top. Notify BLM & NMOC 24 hours prior to testing, Run MIT to 500# for 30min.

APPROVED TO TA FOR 90 DAYS AFTER THAT TIME WELL MUST
BE P&A AS PER APPROVED SUNDRY TO P&A DATED 11/30/10

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Matt Burnham

Title

Engineer

Date

11/1/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

J.D.W. Hittler

Title

LRET

Date

12/2/10

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

CFD

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Occidental Permian Ltd.

NHSAU 443-30

30-025-28958

1300' FSL and 160' FEL

Unit P Section 30, T18S, R38E

Lea County, New Mexico

13 3/8" @ 40' with cmt to surface

8 5/8", 32# & 24#, K-55, ST&C @ 1513' with
625 sx cmt. Did not circulate.
TOC @ 89'. RU 1" and cemented to surface
with Class C "Neat"

DV Tool @ 3152' with 440 sx cmt

105 jts, 5 1/2", 14#, K-55 ST&C @ 4370'
1st Stage: 260 sx cmt
2nd Stage: 440 sx cmt. Did not circulate cmt.
TOC @ 858' by CBL 01/17/1985

San Andres Open Perforations
4167' - 4183', 4191' - 4208', 4223' - 4235',
4240' - 4242', 4245' - 4247', 4257' - 4261', 4265' - 4267'

PBTD 4310'
TD 4370'

TOF @ 4236' (21' of 2 7/8" tubing and 48' of ESP)

Occidental Permian Ltd.

NHSAU 443-30

30-025-28958

1300' FSL and 160' FEL

Unit P Section 30, T18S, R38E

Lea County, New Mexico

13 3/8" @ 40' with cmt to surface

8 5/8", 32# & 24#, K-55, ST&C @ 1513' with
625 sx cmt. Did not circulate.

TOC @ 89'. RU 1" and cemented to surface
with Class C "Neat"

Red Beds	230
Rustler	1450
Salt	1590
Yates	2655
Seven Rivers	2856
Bowers	3300
Queen	3395
Byers	3570
Grayburg	3707
San Andres	3990

DV Tool @ 3152' with 440 sx cmt

105 jts, 5 1/2", 14#, K-55 ST&C @ 4370'

1st Stage: 260 sx cmt

2nd Stage: 440 sx cmt. Did not circulate cmt.

TOC @ 858' by CBL 01/17/1985

San Andres Open Perforations

4167' - 4183', 4191' - 4208', 4223' - 4235',
4240' - 4242', 4245' - 4247', 4257' - 4261', 4265' - 4267'

Set CIBP @ 4100'. Dump bail 8 sx cmt on top.
Tag.

TOF @ 4236'

PBTD 4310'
TD 4370'