Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-HOBBS
RIOR RECEIV

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS DEC 2 2 2016. If Indian, Allottee or Tribe Name

Do not use this i abandoned well.	orm for proposals to dril Use Form 3160-3 (APD) f	or to re-enter an or such proposals	SOCD	·			
SUBMIT IN TRIPLICATE – Other instructions on page 2.				7. If Unit of CA/Agreement, Name and/or No.			
1. Type of Well ☐ Gas Well ☐ Other				8. Well Name and No. Federal "26A" No. 4			
2. Name of Operator Fasken Oil and Ranch, Ltd.				9. API Well No. 30-025-39809			
3a. Address 303 West Wall St., Suite 1800, Midland, TX 797	one No. <i>(include area cod</i> 37-1777	1	10. Field and Pool or Exploratory Area Corbin; Queen, South (Oil) & EK; Delaware				
4. Location of Well (Footage, Sec., T., 1525' FSL & 300' FEL, Section 26, T18S, R33E	R.,M., or Survey Description)	No. 1. 1	11. Count Lea, NM	ry or Parish, Sta	ate /		
12. CHEC	K THE APPROPRIATE BOX(ES)	ΓΟ INDICATE NATURE	OF NOTICE, REPOR	RT OR OTHER	DATA	***************************************	
TYPE OF SUBMISSION		TYF	E OF ACTION				
Notice of Intent ✓ Subsequent Report	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	etruction Recomplete		Water Shut-Off Well Integrity Other Total Depth 8		
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	☐ Temporarily Ab ☐ Water Disposal	andon	Production Casi	ig	
determined that the site is ready fo 8-20-10 - 8-27-10 Drilled a 7 7/8" hole from 1655' - 60 Cemented w/ 1st Stage: 10 bfw, 50 (s.w. 13.2 ppg, yield 1.60 ft3/sx). PI bfw, 525 sx Lite "C" with 6% gel, 1/4 and 0.25% R-38 (s.w. 14.8 ppg, yiel bomb and closed DV tool. WOC tim 5-1/2" csg and 5000 psi flowtree at 2	00'. TD @ 6000'. RIW w/ 135 jts 0 gallons Mud Flush, 10 bfw, 550 0 at 6:00 pm CDT 8-26-10. Press # celloflake, 0.25% R-38, and 5% d 1.35 ft3/sx). Plug down 2:30 ar e 72 hrs. Used 25 centralizers fo 2500 psi and held ok for 20 minute	. 5-1/2" 15.5# J-55 LT& sx Starbond H with 0.6 sured up to 1900 psi, op salt (s.w. 12.4 ppg, yie n CDT 8-14-10, differen r the 5 ½" production ca	C casing @ 5988' al % C-12, 0.25% C-4! lened DV tool and ci ld 2.10 ft3/sx) plus 2 tial pressure 1020 p	nd 1 Weatherf 5, 3 lbs/sx Gils rculated 98 sx 200 sx class "C si. Circulated	ord DV tool @ 3374'. conite, 0.25% R-38, and cement to bins. 2nd Ste " with 2% Calcium Chlo 72 sx cement to bins. 1	3% salt age: 20 ride Oropped	
14. I hereby certify that the foregoing is t Name (Printed/Typed) Kim Tyson	rue and correct.	Title Regulator	y Analyst				
Signature Kim Vynam		Date 11/19/20	10	ACCEP	TED FOR REC	<u> JORE</u>	
	THIS SPACE FOR I	FEDERAL OR STA	TE OFFICE US	E			
Approved by .		Title		Date	DEC 1 8 2010		
Conditions of approval, if any, are attached that the applicant holds legal or equitable t		rant or certify			Long MANAGE	MENIT	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of the United States any false,

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)