

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

JAN 19 2011
HOBBSD

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. <input checked="" type="checkbox"/> 30-025-33201
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 306907
7. Lease Name or Unit Agreement Name Caprock Maljamar Unit
8. Well Number 209
9. OGRID Number 270265
10. Pool name or Wildcat Maljamar; Grayburg-San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4114 GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
SandRidge Exploration and Production LLC

3. Address of Operator
2130 W. Bender Hobbs, NM 88240

4. Well Location
Unit Letter N : 949 feet from the South line and 1700 feet from the West line
Section 20 Township 17S Range 33E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Squeeze Yates Perfs ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU
2. Set RBP @4050/ & cap w/30'sand
3. Spot 100 sxs cement 3650-2650
4. Pull out of cement
5. Pressure up on casing to 750 psi
6. Shut in overnight
7. Drill out cement & test to 300 psi
8. Wash sand off RBP
9. Pull RBP and return to production in the Grayburg-San Andres

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Sr. Regulatory Analyst

DATE 1-17-2011

Type or print name Colleen Robinson

E-mail address: crobinson@sandridgeenergy.com

PHONE: 738-1739

For State Use Only

APPROVED BY:

TITLE

PETROLEUM ENGINEER

DATE

JAN 20 2011

Conditions of Approval (if any):