For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office,

Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Type of action: 🛛 Permit 🗌 Closure

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a closed-loop system that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, please submit a Form C-144. Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

L. Operator: Cimaray Energy Co	
Operator: <u>Cimarex Energy Co.</u> Address: <u>600 N. Marienfeld St., Ste. 600; Midland, TX 79701</u>	OGRID #:162683
Facility or well name:Querecho 36 State Com_No. 1	
API Number: <u>30-025-40064</u> OCD Pern	QI MAGAS
U/L or Qtr/Qtr Section36 Township18S Range32E _ Co	
Center of Proposed Design: Latitude 32° 42' 36.892" Longitude 103° 4	4 <u>3' 37.455"</u> NAD: □1927 🛛 1983
Surface Owner: D Federal State Private Tribal Trust or Indian Allotment	
 2. Closed-loop System: Subsection H of 19.15.17.11 NMAC Operation: Drilling a new well Workover or Drilling (Applies to activities wh Above Ground Steel Tanks or Haul-off Bins 	ich require prior approval of a permit or notice of intent) 🔲 P&A
3.	
Signs: Subsection C of 19.15.17.11 NMAC	An
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency te ☐ Signed in compliance with 19.15.3.103 NMAC	elephone numbers
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of Instructions: Each of the following items must be attached to the application. Plea attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of Closure Plan (Please complete Box 5) - based upon the appropriate requirement OPERATION OPERATION OPERATION OPERATION Previously Approved Design (attach copy of design) API Number: Previously Approved Operating and Maintenance Plan API Number:	ise indicate, by a check mark in the box, that the documents are 19.15.17.12 NMAC its of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
5. Waste Removal Closure For Closed-loop Systems That Utilize Above Ground St	eel Tanks or Haul-off Bins Only: (10:15 17 13 DNMAC)
Instructions: Please indentify the facility or facilities for the disposal of liquids, dri	illing fluids and drill cuttings. Use attachment if more than two
facilities are required.	n an ann ann an an an an an an an an an
	isposal Facility Permit Number: <u>R-9166</u>
	isposal Facility Permit Number:
Will any of the proposed closed-loop system operations and associated activities occu Yes (If yes, please provide the information below) X No	ir on or in areas that will not be used for future service and operations?
Required for impacted areas which will not be used for future service and operations. Soil Backfill and Cover Design Specifications based upon the appropriate re Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 c Site Reclamation Plan - based upon the appropriate requirements of Subsection	equirements of Subsection H of 19.15.17.13 NMAC
6. Operator Application Certification:	ан на н
I hereby certify that the information submitted with this application is true, accurate a	and complete to the best of my knowledge and belief.
Name (Print): Natalie Krueger	Title:Regulatory
Signature: Watalikhuger	Date: 2.17.2011
e-mail address:nkrueger@cimarex.con	Telephone: 432-620-1936
Form C-144 CLEZ Oil Conservation Di	vision Page 1 of 4

· .		
	· .	
CD Approval: Permit Application (including	closure plan) 🗌 Closure Plan (only)	
CD Representative Signature:		Approval Date: 02/17/1/
tle: <u> </u>	Ologist OCD Permit Number	PI-02928
structions: Operators are required to obtain an a se closure report is required to be submitted to the	re completion): Subsection K of 19.15.17.13 NMA(approved closure plan prior to implementing any close e division within 60 days of the completion of the clo has been obtained and the closure activities have bee	sure activities and submitting the closure repor sure activities. Please do not complete this en completed.
· · · · ·		tion Date:
Closure Report Regarding Waste Removal Closur istructions: Please indentify the facility or faciliti vo facilities were utilized.	<u>re For Closed-loop Systems That Utilize Above Gr</u> es for where the liquids, drilling fluids and drill cutt	ound Steel Tanks or Haul-off Bins Only: ings were disposed. Use attachment if more the
Disposal Facility Name:		it Number:
Disposal Facility Name:		it Number:
Vere the closed-loop system operations and associat Yes (If yes, please demonstrate compliance to	ed activities performed on or in areas that will not be the items below) \square No	used for future service and operations?
Required for impacted areas which will not be used f Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding		
Pperator Closure Certification: hereby certify that the information and attachments elief. Lalso certify that the closure complies with at	submitted with this closure report is true, accurate an l applicable closure requirements and conditions spec	d complete to the best of my knowledge and
ame (Print):	Title:	
gnature:	Date:	
mail address:	Telephone:	
		с. С. С. С
		······ ·······························

Cimarex Energy Co. – Closed-Loop System Design Plan

Equipment List

- Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 or 2 Centrifuges (depending on well depth)
- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

Operation and Maintenance

The Cimarex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

Closure Plan

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).

Page 3 of 4



Oil Conservation Division

