

Submit 1 Copy To Appropriate District Office
District I
1625 N. C. Street, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brizos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr. Santa Fe, NM 87505
HOBBSOCD

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-32805
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-1113-1
7. Lease Name or Unit Agreement Name Central Vacuum Unit
8. Well Number 200
9. OGRID Number 4323
10. Pool name or Wildcat Vacuum Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other Injector ☐	
2. Name of Operator Chevron U. S. A.	
3. Address of Operator 15 Smith Road	
4. Well Location Unit Letter C : 1236 feet from the North line and 1875 feet from the West line Section 6 Township 18-S Range 35-E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3975' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Wellhead repair

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Well failed the annual bradenhead test on 11/9/10. Chevron plans to investigate the cause of the leak and restore the mechanical integrity of the well if it is economically viable.

Per Underground Injection Control Program Manual
11.6 C Packer shall be set within or less than 100
feet of the uppermost injection perfs or open hole.

Condition of Approval: Notify OCD Hobbs
office 24 hours prior of running MIT Test & Chart

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Paul T. Brown TITLE Petroleum Engineer DATE 3/2/11

Type or print name Paul T. Brown E-mail address: paulbrown@chevron.com PHONE: 432=687-7351
For State Use Only

APPROVED BY [Signature] TITLE State MIT DATE 3-3-2011
Conditions of Approval (if any):

CoH

**CURRENT
WELLBORE DIAGRAM**

CVU 200

Created: 4/9/2009 By: Cayce
 Updated: By:
 Updated: By:
 Lease: Central Vacuum Unit
 Surface Location: 1236' FNL & 1875' FWL
 Bottomhole Location:
 County: Lea St: NM
 Current Status: Active Water Injection
 Directions to Wellsite:

Well No.: 200
 Unit Ltr: C
 Unit Ltr:
 St Lease:
 Elevation: 3975' GR

Field: Vacuum Grayburg San Andres
 Sec: 6 TSHP/Range: 18S 35E
 Sec: TSHP/Range:
 API: 30-025-32805 Cost Center:
 CHVNO: TEPI:
 MVP:

Surface Csg.

Size: 8-5/8"
 Wt.: 24# WC-50 STC
 Set @: 1524'
 Sxs cmt: 525
 Circ: Yes
 TOC: surface
 Hole Size: 11'

KB: 3989'
 DF: 3988'
 GL: 3975'

Original Spud Date: 3/18/1995
 Original Compl. Date: 4/7/1995

Well History

3/18/95 Spud
 4/95 Begain injection of water
 1/96 Casing test
 12/97 CO 4453-4760, acidize perfs 4253-4661 w/10M gals + 6000# RS,
 flowed back. Performed MIT.
 4/98 Cross well tomography
 6/99 Performed MIT
 11/06 MIT failure. CO 4209-4714', bad csg in perfs, mill 4455-4605, tight
 spot 4466-70, milled. c/o to 4794'. Perf 4756-4776, 4738-4756, 4689-4709,
 4669-4689, 4663-4669. Acidize 4253-4776 w/5000 gals 15% acid. TIH
 w/mill & tag @ 4722'. c/o 4722-4794.
 3/09 Bad tbq valve

Production Csg.

Size: 5-1/2"
 Wt.: 15.5# WC-50 LTC
 Set @: 4850'
 Sxs Cmt: 812
 Circ: yes
 TOC: surface
 Hole Size: 7 7/8'

Packer @ 4171' with
 1.50 "F" profile

Perfs 4256-4776'

Perforation detail:

4256-59, 62-65, 70-73, 77-78, 4308-15, 15-18, 19-20, 22-24, 40-
 44, 48-53, 56-62, 70-80, 83-85, 87-92, 94-95, 4398-4401, 03-05, 07-
 18, 26-31, 41-51, 54-69, 88-89, 91-99, 4506-18, 21-27, 29-36, 38-
 43, 48-54, 57-58, 66-68, 71-80, 84-88, 90-93, 96-98, 4600-4602',
 4608-4610', 4623-4625', 4636-4637', 4663-4669, 4669-4689,
 4689-4709, 4738-4756, 4756-4776

PBTD: 4786'
 TD: 4850'