

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

RECEIVED
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
MAR 17 2011
HOBBS

WELL API NO. 30-025-40000
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Zebra 16 State Com
8. Well Number 1 H
9. OGRID Number 14744
10. Pool name or Wildcat Vacuum; Abo, North 61760
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3330' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter M : 330' feet from the South line and 385' feet from the West line
Section 16 Township 17S Range 35E NMPM Lea County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/23/11...MI & spud 17 1/2" hole. Ran 460' 13 3/8" 48#, H40 ST&C csg. Cemented with 500 sks Class "C" w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 1:30 pm 02/24/11. Circ 124 sks cmt to pit. At 7:00 am 02/25/11 tested BOPE t& csg to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

02/27/11. TD'ed 12 1/4" hole @ 1800'. Ran 1800' 9 5/8" 36# J55 LT&C Csg. Cemented with 400 sks EconoCem-HLC w/additives. Mixed @ 12.6# /g w/1.99 yd. Tail w/200 HalCem-C w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.35 yd. Plug down @ 6:00 pm 02/26/11. Circ 106 sks cement to pit. WOC 18 hrs. 02/27/11 tested BOPE & csg to 1500# for 30 minutes, held OK.

Spud Date: 02/23/2011

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/09/11

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE PETROLEUM ENGINEER DATE MAR 15 2011

Conditions of Approval (if any):