Submit 1 Copy To Appropriate District Office District I State of New Mexico Energy, Minerals and Natural Resources	Form C-103 October 13, 2009
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210 District III MAR 2 51220 South St. Francis Dr.	30-025-39941 / 5. Indicate Type of Lease ,
	STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 HOBBS () Santa Fe, NM 87505	6. State Oil & Gas Lease No. VB-1384
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	7. Lease Name or Unit Agreement Name Blackberry BKB State 8. Well Number
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	1H
2. Name of Operator	9. OGRID Number
Yates Petroleum Corporation 3. Address of Operator	025575 / 10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	Berry; Bone Spring, North
	330 feet from the East line 2310 feet from the East line
Section 6 Township 21S Range 34E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3727'GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A	
TEMPORARILY ABANDON	
DOWNHOLE COMMINGLE	
OTHER: OTHER: Producti	ion casing
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
3/7/11 – TD 8-3/4" hole to 10,150'.	
3/8/11 - Set 1 st cement plug from 9942'-9750' with 128 sx Class "H" Neat cement with additives.	
3/9/11 – Set 2 nd cement plug from 9469'-9150' with 165 sx Class "H" Neat cement with additives. TOOH to 8750'. Circulated. Set kick off plug from 8750'-8150' with 434 sx Class "H" cement and additives. TOOH to 7600'. Circulated and WOC.	
3/10/11 - Tagged cement at 8010'. Drilled cement to 8383'. Still drilling 100% cement. KOP at 83	77' and continued to drill directionally.
3/17/11 – TD 8-1/2" hole to 13,237' at 3:00 PM. 3/18/11 – Set 5-1/2" 17# HCP-110 LT&C casing at 13,237'. Stage tool at 7003'. Float collar at 13,1-	47'. Cemented stage 1 with 230 sx 35:65:6 Poz "C"
+ 0.887#/sx D112 + 0.125#/sx D130 + 27.65#/sx D132 + 0.02#/sx D177 + 5.325#/sx D20 + 4.785#/s; D42 (yld 2.08, wt 12.6). Tailed in with 1050 sx PVL + 0.9#/sx D112 + 22.5#/sx D151 + 75#/sx D49	
Drop bomb and open DV tool. Circulated 325 sx off DV tool. Cemented stage 2 with 300 sx 35:65:6	6 Poz "C" + 0.887#/sx D112 + 0.125#/sx D130 +
27.65#/sx D132 + 5.325#/sx D20 + 4.785#/sx D44 + 61.1#/sx D903 + 0.177#/sx D46 + 2.0#/sx D42 (yld 2.08, wt 12.6). Tailed in with 100 sx Class "C" + 94#/sx D903 + 0.188#/sx D13 (yld 1.33, wt 14.8). No sacks circulated to pit.	
3/20/11 – Rig released at 2:00 PM.	
2/7/11	2/20/11
Spud Date: 2/7/11 Rig Release Date:	3/20/11
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE TITLE Regulatory Compliance Supervisor DATE March 24, 2011	
Type or print name Tina Huerta E-mail address: tinah@yatespetroleun For State Use Only	
APPROVED BY: Conditions of Approval (If any):	MAR 2 8 2011 DATE