

RECEIVED

APR 05 2011

HOBSOCD

## OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-24812

5. Indicate Type of Lease

STATE ☒FEE ☐

6. State Oil &amp; Gas Lease No.

VO-5562

7. Lease Name or Unit Agreement Name

Meteor BEM State

8. Well Number

1

9. OGRID Number

025575

10. Pool name or Wildcat

Eight Mile Draw; Abo

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other P&A

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter F : 1980 feet from the North line and 1980 feet from the West lineSection 23 Township 11S Range 34E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4144GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/28/11 – Released packer. NU BOP.

3/29/11 – Set 5-1/2" CIBP @ 8930'. Tagged CIBP. Loaded and tested casing to 500 psi.

3/30/11 – Spotted 25 sx "H" neat cement on CIBP 8930'. Calculated TOC to be 8704'. Perforated 4 holes at 6000'. Pressured to 600 psi. Spotted 25 sx "C" neat cement with 3% CaCl @ 6068'. WOC 4 hours. Tagged at 5820'. Perforated 4 holes @ 4270'. Pressured to 700 psi. Spotted 25 sx "C" neat cement @ 4330'. Calculated TOC to be 4077'. WOC.

3/31/11 – Tagged plug @ 4090'. Perforated 4 holes @ 2150'. Circulated out 8-5/8" X 5-1/2". Pumped 40 sx "C" neat cement with 3% CaCl. WOC 4 hours. Tagged @ 2000'. Perforated 4 holes @ 400'. Pumped 107 sx "C" neat cement. Circulated to surface. ND BOP. Dug out cellar, cut off wellhead, and installed dry hole marker. Filled cellar, cut anchors, and cleaned location.

**WELL IS PLUGGED AND ABANDONED.**


Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
www.cmnr.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

Regulatory Compliance Technician

DATE

April 1, 2011

Type or print name

Craig Aton

E-mail address:


caton@yatespetroleum.com

PHONE:

575-748-4385

For State Use Only

APPROVED BY:



TITLE

STATE MGR

DATE

4-6-2011

Conditions of Approval (if any):