| Office District I 1625 N. French Dr., Hobbs, REGEIVED District II | State of New Mexico | Form C-103 | | |
|--|--|--|--|--|
| | Minerals and Natural Resources | October 13, 2009 WELL API NO. | | |
| District II | A | 30-025-31194 | | |
| 1301 W. Grand Ave., Artesia, NM 88210 October OIL Co | ONSERVATION DIVISION | 5. Indicate Type of Lease | | |
| 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 | 220 South St. Francis Dr. | STATE FEE | | |
| District IV | Santa Fe, NM 87505 | 6. State Oil & Gas Lease No. | | |
| District IV 1220 S. St. Francis Dr., San HOBBSUUU | | | | |
| 87505 SUNDRY NOTICES AND RE | DODTE ON WELLE | 7 Land Name III is a | | |
| (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL | | 7. Lease Name or Unit Agreement Name | | |
| DIFFERENT RESERVOIR. USE "APPLICATION FOR PER | | JUNK YARD DOG | | |
| PROPOSALS.) | | 8. Well Number | | |
| 1. Type of Well: Oil Well Gas Well | Other | / | | |
| 2. Name of Operator PRIMAL ENERGY CORPORT | /AGITA | 9. OGRID Number 154303 | | |
| 3. Address of Operator | MIIO 0 | 10. Pool name or Wildcat | | |
| • | Va 50014 V 74 7772779 | _ | | |
| 21021 SPRINGBROOK PLAZA DR, SUITE | 160) 2451MR 1X 11/ 21/ | JALMAT TANSILL YATES 7 RIVER | | |
| 4. Well Location Unit Letter : 660 fee | . N | 360 feet from the W line | | |
| Unit Letter : 660 feet | t from theline and | | | |
| | wnship 25-S Range 37-E | NMPM LEA County NM | | |
| 11. Elevation | n (Show whether DR, RKB, RT, GR, etc | :.) | | |
| 2101 | 5'GK | | | |
| , | • | | | |
| 12. Check Appropriate I | Box to Indicate Nature of Notice | , Report or Other Data | | |
| | • | | | |
| NOTICE OF INTENTION | | SSEQUENT REPORT OF: | | |
| PERFORM REMEDIAL WORK PLUG AND | | | | |
| TEMPORARILY ABANDON CHANGE PL | | RILLING OPNS. P AND A | | |
| PULL OR ALTER CASING MULTIPLE C | COMPL CASING/CEMEN | NT JOB [| | |
| DOWNHOLE COMMINGLE | | | | |
| OTHER: | CT OTHER | П | | |
| 13. Describe proposed or completed operation | OTHER: | nd give pertinent dates, including estimated de- | | |
| | w. Charry state an pertinent details, at | oo erva nammen omes mending esimalen og | | |
| of starting any proposed work) SEF RIII | E 19 15 7.14 NMAC For Multiple Co | ampletions: Attach wellhore diagram of | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment | t. Dug out cellar. ND wellhead and | ompletions: Attach wellbore diagram of NU BOP. Well started flowing. Pumped | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Cs brine down back side. Went on va BP on tbg and set @ 2715'. Circular POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur S'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure ad and welded on Dry Hole Market Rig Release Date: | NU BOP. Well started flowing. Pumped Closed well in shut down. Icum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Ited up on casing held 1000 psi for 20 of sx class C cement. displaced to 1295'. Is C cement and displaced to 510'/ Closed face plug. Rigged down moved off. Icur. Cut off deadmen. Backfilled cellar and coved for plugging of well bere only. It winder bond is retained pending receipt 103 (Subsequent Report of Well Plugging) | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOI Moved in backhoe and welder. Cut off wellhe cleaned location. Moved off. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Cs brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur S'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement suread and welded on Dry Hole Market Rig Release Date: Approximately a strength of Calibrian Calibrian Rig Release Date: | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 26 sx class C cement. displaced to 1295'. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 25 sx o | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOF Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Cest brine down back side. Went on various BP on tbg and set @ 2715'. Circular POH to 1500'. Closed well in shut down and set packer @ 34'. Pressur St. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately a set of my knowledge and complete to the best of my knowledge and complete | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 25 sx own. Interded hole w/ mud laden fluid. Spot 26 sx class C cement. displaced to 1295'. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 26 sx own. Interded hole w/ mud laden fluid. Spot 25 sx o | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOF Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Cest brine down back side. Went on various BP on tbg and set @ 2715'. Circular POH to 1500'. Closed well in shut down and set packer @ 34'. Pressur St. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately a set of my knowledge and complete to the best of my knowledge and complete | NU BOP. Well started flowing. Pumped closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sx class C cement. displaced to 1295'. In sx class C cement. displaced to 510'/ Closed Interpolation of well beautiful or control of the contr | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: Type or print name CASES FUNKHOUS For State Use Only APPROVED BY: APPROV | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |
| of starting any proposed work). SEE RUL proposed completion or recompletion. 02/08/11 MIRU rig and cementing equipment bbls fresh water down tbg and pressured up. 02/09/11 Bled down casing. Pumped 100 bbls 02/10/11 POH w/ 90 jts. tbg. RIH w/ 5 1/2 CI class C cement on top of CIBP (2715-2460). P 02/11/11 Tagged plug @ 2412'. POH w/ tbg. minutes. Pulled packer. Perf'd casing @ 1405 WOC. Tagged plug @ 1225'. POH w/ tbg. Pewell in w/ 700 psi. 02/14/11 Tagged plug @ 426'. POH. ND BOH Moved in backhoe and welder. Cut off wellhed cleaned location. Moved off. Spud Date: I hereby certify that the information above is true and significant properties. | t. Dug out cellar. ND wellhead and Pumped 120 bbls down annulus. Os brine down back side. Went on va BP on tbg and set @ 2715'. Circula POH to 1500'. Closed well in shut do RIH and set packer @ 34'. Pressur 5'. RIH w/ packer to 1100'. Sqz'd 30 rf'd casing @ 610'. Sqz'd 45 sx class P. Pumped 15 sx class C cement sure and and welded on Dry Hole Market Rig Release Date: Rig Release Date: Approximately and complete to the best of my knowledge and complete and complete to the best of my knowledge and complete and c | NU BOP. Well started flowing. Pumped Closed well in shut down. Incum. Shut well in. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inted hole w/ mud laden fluid. Spot 25 sx own. Inter up on casing held 1000 psi for 20 In sx class C cement. displaced to 1295'. In sc C cement and displaced to 510'/ Closed of the start and displaced to 510'/ Closed of the start and the start and the start and start and the start | | |

.

Form¶160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

APR 19 2011

RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010
5. Lease Serial No.

LC 032581 - A


| SUNDRY NOTICES | AND REPORTS ON | WELLSOSOCO |
|--|--------------------------|------------|
| SUNDRY NOTICES Do not use this form for | proposals to drill or to | いたのかかっ |

| Do not use this form for proposals to drill or to re-to-band abandoned well. Use Form 3160-3 (APD) for such proposals. | | | | 6. If Indian, Allottee or Tribe Name |
|--|--|--|--|---|
| SUBMIT IN | 7. If Unit or CA/Agreement, Name and/or No. | | | |
| 1. Type of Well | | | , , , <u>, , , , , , , , , , , , , , , , </u> | |
| Oil Well Gas Well | Other | | | 8. Well Name and No. |
| 2. Name of Operator | | | | Junk Yard Dog #1 |
| Primal Energy Corporation | l | | | 9. API Well No. |
| 3a. Address | | 3b. Phone No. (include are | ea code) | 30-025-31194 |
| 21021 Springbrook, #160, S | | | | 10. Field and Pool, or Exploratory Area |
| 4. Location of Well (Footage, Sec., T., R. | | tion) | | Jalmat Tansill Yates 7 Rivers |
| Unit Letter D, 660 FNL & 360 FWL | | | 11. County or Parish, State | |
| Sec. 19, T-25-S, R-37-E, Lea | | rano eo mena e | NATIOE OF NOTICE | Lea Co. NM |
| | PROPRIATE BOX | (ES) TO INDICATE | | REPORT, OR OTHER DATA |
| TYPE OF SUBMISSION | | | TYPE OF ACTIO | N |
| | Acidize | Deepen | Production (Start/R | lesume) Water Shut-Off |
| Notice of Intent | Alter Casing | Fracture Treat | Reclamantion | Well Integrity |
| Subsequent Report | Casing Repair | New Construction | on Recomplete | Other |
| · · | Change Plans | Plug and Aband | on Temporarily Abanc | ion |
| Final Abandonment Notice | Convert to Injection | n Plug Back | Water Disposal | |
| bbls fresh water down the a 02/09/11 Bled down casing. 02/10/11 POH w/ 90 jts. the class C cement on top of CI 02/11/11 Tagged plug @ 24 minutes. Pulled packer. Per WOC. Tagged plug @ 1225 well in w/ 700 psi. 02/14/11 Tagged plug @ 42 Moved in backhoe and weld cleaned location. Moved off | and pressured u. Pumped 100 bl g. RIH w/ 5 1/2 (BP (2715-2460). 12'. POH w/ tbg- f'd casing @ 14 '. POH w/ tbg. l 6'. POH. ND Bo der. Cut off well | p. Pumped 120 bbl bls brine down bac CIBP on tbg and se POH to 1500'. Clo g. RIH and set pack 05'. RIH w/ packet Perf'd casing @ 610 OP. Pumped 15 sx | Is down annulus. Clos k side. Went on vacuate et @ 2715'. Circulated osed well in shut down ker @ 34'. Pressured r to 1100'. Sqz'd 30 sx 0'. Sqz'd 45 sx class C | m. Shut well in. I hole w/ mud laden fluid. Spot 25 sx |
| 14. I hereby certify that the foregoing is Name (<i>Printed/Typed</i>) | true and correct.) | | 1 | |
| | KHOUSER | | Title CEO | |
| Signature | | | Date 3-2-20 | 11 |
| | THIS SPA | CE FOR FEDERA | AL OR STATE OFFI | |
| | | | . | |
| Approved by | | | Title | Date |
| Conditions of approval, if any, are attached the applicant holds legal or equitable title applicant to conduct operations thereon. | to those rights in the six | bject lease which would enti | itle the Office | |
| Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent st | U.S.C. Section 1212, n | pake it a crime for any person | n knowingly and willfully to ma | ke to any department or agency of the United |

TUNK YARD DOG PRE-PHA WELL SQ TYPE OF TUBING DEPTH 2958 NO.JTS. 92 TO SEATING NIPPLE DEPTHAONE NO.JTS, TO PERF. NIPPLE MONG BRAND TYPE TUBING ANCHOR - DEPTHARKE NO.JTS._____TO____'MUD ANCHOR 3025-111 NO. JTS BOTTOM OF STRING LENGTH With 1. Collon. 2957 REPLACEMENT . RODS ROD SIZE NO. RODS TYPE BOX MAKE & GRADE NEW USED DERRICK ELEVATION_ PBTD JOSS

CSG.SIZE

JUNK YARD DOG #1 POST PHA WELL SCHEMATIC



PRIMAL ENERGY CORPORATION

21021 SPRINGBROOK PLAZA DRIVE, SUITE 160 SPRING, TEXAS 77379 281-821-5600, X104 281-821-5602 fax c.funkhouser@primalenergy.net

April 13, 2011

RECEIVED

New Mexico EMNRD District I Office 1625 N. French Dr. Hobbs, NM 88240 APR 19 ZUTI

Reference:

Junk Yard Dog #1 P&A

To Whom It May Concern:

Primal Energy Corporation has plugged and abandoned the Junk Yard Dog #1 well (API # 30-025-31194) located in Section 19, Township 25 South, Range 37 East, NMPM, Lea County, New Mexico. Enclosed herewith please find for EMNRD approval Primal Energy's Form C-103 Subsequent Report of P&A, Form C-103 Location Ready for OCD Inspection after P&A and Form C-144 CLEZ Closure Report. I have also included a copy of the federal form we are submitting to the BLM for your reference. If you have any questions or need anything else please do not hesitate to contact me.

Sincerely,

PRIMAL ENERGY-CORPORATION

Casey Funkhouser

Enclosures:

Form C-103 Subsequent Report of P&A

Form C-103 Location Ready for OCD Inspection after P&A

Form C-144 CLEZ Closure Report

BLM Form 3160-5