Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
District I 1625 N. Franch Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources	October 13, 2009 WELL API NO.
District II	OIL CONSERVATION DIVISION	30-005-29160
District III AVe., Artesia, NM 88210	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE X FEE
District IV	BSOCB anta Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
SUNDRY NOTICES	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS DIFFERENT RESERVOIR. USE "APPLICATIO PROPOSALS.)	TO DRILL OR TO DEEPEN OR PLUG BACK TO A ON FOR PERMIT" (FORM C-101) FOR SUCH	Rock Queen Unit
1. Type of Well: Oil Well Gas	Well 🗌 Other Injection	8. Well Number 702
2. Name of Operator Celero Energy II,	LP	9. OGRID Number 247128
3. Address of Operator 400 W. Illinois, Midland, TX 7	Ste. 1601	10. Pool name or Wildcat
4. Well Location	<i></i>	Caprock; Queen
Unit Letter C : 100	feet from the North line and 26	28 feet from the West line
Section 36	Township 13S Range 31E	NMPM CountyChaves
	Elevation (Show whether DR, RKB, RT, GR, etc.	
4.	390'	
12. Check Appro	opriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTEN	NTION TO: SUE	SEQUENT REPORT OF:
	UG AND ABANDON 🔲 🛛 🛛 REMEDIAL WOF	K 🗌 ALTERING CASING 🗌
		ILLING OPNS. P AND A
		IL JOB
OTHER:	OTHER: Well Co	mpletion
13. Describe proposed or completed	operations. (Clearly state all pertinent details, ar	d give pertinent dates, including estimated date
13. Describe proposed or completed	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co	d give pertinent dates, including estimated date
13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion3/24 - 3/30/11	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion.	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic 1 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of us WS w/ 6- 3 1/8" OD DC's + 4 ³ / ₄ " bit. Ran &
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompleted 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic 1 tag @ 3077'. C/O from 3069' - 3082'. (SPF, 120° phasing, 0.4" hole from 304 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of us WS w/ 6- 3 1/8" OD DC's + 4 ³ / ₄ " bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'.
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompleted 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic 1 tag @ 3077'. C/O from 3069' - 3082'. C SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of us WS w/ 6- 3 1/8" OD DC's + 4 ³ / ₄ " bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers &
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompleted 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic 1 tag @ 3077'. C/O from 3069' - 3082'. C SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p flushed w/ 15 BPW w/ 1 bbl of overflu 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380#	ad give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 $\frac{3}{4}$ " bit. Ran & 3082'. Perf 5 $\frac{1}{2}$ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 $\frac{1}{2}$ " AD-1 pkr. Ran & set @ 2948'. f 7 $\frac{1}{2}$ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min =
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion and the second starting (a) 3077'. C/O from 3069' - 3082'. Completion SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p flushed w/ 15 BPW w/ 1 bbl of overflution 565#; 10 min = 195#; 15 min = 115#; out of well. Release pkr, lwr pkr through the second starting in the second starting is second starting and the second starting at the second starting at the second starting at the second starting a	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO	In d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 $\frac{3}{4}$ " bit. Ran & 3082'. Perf 5 $\frac{1}{2}$ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 $\frac{1}{2}$ " AD-1 pkr. Ran & set @ 2948'. f 7 $\frac{1}{2}$ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion or recompletion of the start of the s	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant	ad give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 $\frac{3}{4}$ " bit. Ran & 3082'. Perf 5 $\frac{1}{2}$ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 $\frac{1}{2}$ " AD-1 pkr. Ran & set @ 2948'. f 7 $\frac{1}{2}$ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 $\frac{1}{2}$ " AS1-X nickel plated pkr. Set pkr @
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompleted 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic I tag @ 3077'. C/O from 3069' - 3082'. O SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p flushed w/ 15 BPW w/ 1 bbl of overflu 565#; 10 min = 195#; 15 min = 115#; out of well. Release pkr, Iwr pkr throug (3010') of 2 3/8" OD 4.7# 8rd EUE J-3 3010'. Release from pkr, circ pkr fluid flanged tbg head w/ 2 1/16" 5K SS tbg 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant w , latch back onto pkr, NDBOP, pulled 20 pts of to g valve & nickel plated injection tee. Connect up	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of s WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ /2" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ /2" AD-1 pkr. Ran & set @ 2948'. f 7 ¹ /2% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ /2" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion and the set of the set	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant , latch back onto pkr, NDBOP, pulled 20 pts of to	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of s WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ /2" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ /2" AD-1 pkr. Ran & set @ 2948'. f 7 ¹ /2% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ /2" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompleted 3/24 - 3/30/11 MIRU. NDBOP & NU 3K Hydraulic I tag @ 3077'. C/O from 3069' - 3082'. O SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p flushed w/ 15 BPW w/ 1 bbl of overflu 565#; 10 min = 195#; 15 min = 115#; out of well. Release pkr, Iwr pkr throug (3010') of 2 3/8" OD 4.7# 8rd EUE J-3 3010'. Release from pkr, circ pkr fluid flanged tbg head w/ 2 1/16" 5K SS tbg 	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant w , latch back onto pkr, NDBOP, pulled 20 pts of to g valve & nickel plated injection tee. Connect up	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of s WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ /2" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ /2" AD-1 pkr. Ran & set @ 2948'. f 7 ¹ /2% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ /2" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion or recompletion of the start of the s	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant w , latch back onto pkr, NDBOP, pulled 20 pts of to g valve & nickel plated injection tee. Connect up	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of s WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ /2" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ /2" AD-1 pkr. Ran & set @ 2948'. f 7 ¹ /2% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ /2" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of the second completion of the second	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant w , latch back onto pkr, NDBOP, pulled 20 pts of ta g valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Rig Release Date:	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of s WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ /2" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ /2" AD-1 pkr. Ran & set @ 2948'. f 7 ¹ /2% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ /2" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of the start of th	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant v , latch back onto pkr, NDBOP, pulled 20 pts of tb g valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Rig Release Date: WFX- 883	ad give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ / ₂ " AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of the second completion of the second	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant v , latch back onto pkr, NDBOP, pulled 20 pts of to y valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Rig Release Date: WFX-883 e is true and complete to the best of my knowledge	ad give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ / ₂ " AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of the start of th	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant v , latch back onto pkr, NDBOP, pulled 20 pts of to y valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Rig Release Date: WFX-883 e is true and complete to the best of my knowledge	ad give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ / ₂ " AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion of the second completion of the second	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant v , latch back onto pkr, NDBOP, pulled 20 pts of to y valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Rig Release Date: WFX-883 e is true and complete to the best of my knowledge	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ / ₂ " AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order ge and belief.
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion or recompleting (a) 3077'. C/O from 3069' - 3082'. C SPF, 120° phasing, 0.4" hole from 304 Load & test tbg-csg annulus w/ 500# p flushed w/ 15 BPW w/ 1 bbl of overflution 565#; 10 min = 195#; 15 min = 115#; out of well. Release pkr, lwr pkr throug (3010') of 2 3/8" OD 4.7# 8rd EUE J-5 3010'. Release from pkr, circ pkr fluid, flanged tbg head w/ 2 1/16" 5K SS tbg (a) 520#. No pressure loss. Witnessed No. R-1541-A Spud Date: Signature Action Start Star	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg pressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant w , latch back onto pkr, NDBOP, pulled 20 pts of tbg gt valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact WFX-883 e is true and complete to the best of my knowledge CA TITLE Regulatory Analyst E-mail address: <a +="" 4="" <sup="" dc's="" href="https://libut.libu</td><td>d give pertinent dates, including estimated date
mpletions: Attach wellbore diagram of
as WS w/ 6- 3 1/8" od="">3/4" bit. Ran & 3082'. Perf 5 ¹/₂" csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹/₂" AD-1 pkr. Ran & set @ 2948'. f 7 ¹/₂% NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹/₂" AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order ge and belief. DATE 04/05/2011 ergy.com PHONE: (432)686-1883	
 13. Describe proposed or completed of starting any proposed work). proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion or recompletion or recompleting (a) 3077'. C/O from 3069' - 3082'. Completion of the set of the set	operations. (Clearly state all pertinent details, ar SEE RULE 19.15.7.14 NMAC. For Multiple Co etion. BOP. TIH w/ 2 3/8" OD 4.7# 8rd EUE J-55 tbg a Circ hole clean. Ran GR/CCL/CNL from 2000' - 45' - 3059'; 15' & 30 holes. TIH w/ 2 3/8" OD tbg poressure. Acdz perfs, 3045' - 3059' w/ 2000 gal o ush. Treating pressures: 3000#; Avg rate = 2380# TLTR = 77 bbls. After SI 61 hrs, TP = 0#. Ran gh perfs 3045-59' & knocked off ball sealers. TO 55 IPC tbg w/ Hunting's special thread lubricant v , latch back onto pkr, NDBOP, pulled 20 pts of tr y valve & nickel plated injection tee. Connect up by Maxey Brown w/ OCD. Original chart is attact Image: Detail of the store of my knowledge TITLE Regulatory Analyst	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of as WS w/ 6- 3 1/8" OD DC's + 4 ³ /4" bit. Ran & 3082'. Perf 5 ¹ / ₂ " csg w/ 3 1/8" cased gun, 2 WS w/ 5 ¹ / ₂ " AD-1 pkr. Ran & set @ 2948'. f 7 ¹ / ₂ % NEFE acid + 40- 7/8" ball sealers & ; Avg rate = 4.0 BPM; ISIP = 1690#; 5 min = swab & tag fluid @ 250' FS. Pulled 3 BFW H w/ tbg WS, LD tbg w/ pkr. TIH w/ 93 jts w/ 5 ¹ / ₂ " AS1-X nickel plated pkr. Set pkr @ ension on pkr. NU 7 1/16" x 3K slip type WH for injection. Ran MIT. Tested for 32 min ched. Well ready for injection as per Order ge and belief. DATE 04/05/2011 ergy.com PHONE: (432)686-1883

-

