## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

**SUNDRY NOTICES AND REPORTS ON WELLS** Do not use this form for proposals to drill or to re-enter an

BCD: Hobby FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

MAY 0 4 2011

	F
5.	Lease Serial No.
	NMNM052

NMNM052	
6. If Indian, Allottee or Tribe Name	

abandoned we										
SUBMIT IN TRI	VED	7. If Unit or CA	/Agreemei	nt, Name and/or No.						
Type of Well     Gas Well □ Oth	ier /		8. Well Name and No. MALLON 35 FED 04							
2. Name of Operator	Contact: N	KRUEGER 9. API Well No.								
CIMAREX ENERGY COMPAI	NY OF C@-Mail: nkrueger@c				30-025-390		,			
3a. Address 600 N MARIENFELD STREE MIDLAND, TX 79701	(include area code 0-1936 -1940	)	10. Field and Pool, or Exploratory  LEA Bene Spring							
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description,	)			<ol><li>County or P</li></ol>	arish, and	State			
Sec 35 T19S R34E SWSW 66 32.611388 N Lat, 103.537434				LEA COUNTY, NM						
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF 1	NOTICE, RI	EPORT, OR O	THER D	DATA			
TYPE OF SUBMISSION		• .	TYPE O	F ACTION						
□ Notice of Intent	□ Acidize	□ Deep	Deepen		☐ Production (Start/Resume)		Water Shut-Off			
_	☐ Alter Casing		ture Treat	□ Reclama		-	Well Integrity			
Subsequent Report	Casing Repair	_	Construction	□ Recomp		Ę	Other Well Spud			
☐ Final Abandonment Notice	Change Plans		and Abandon	Temporarily Abandon			·			
13. Describe Proposed or Completed Ope	Convert to Injection		lug Back Water							
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  11-27-10. Spudded 17.5 inch hole. 12-01-10 Ran 13.375 inch 48# H40 STC @ 1705. Cmt with lead 1000 sx Econocem, tail 200 sx Halcem C, circ 81 bbl, WOC 29.5 hrs, tested to 1200# for 30 min, ok. 12-12-10 In 12.25 inch hole, ran 9.625 inch 40# P110 LTC @ 5502. Cmt with lead 1400 sx Econocem HLC, tail 215 sx Halcem C, circ 124 sx, WOC 44.5 hrs, tested to 1500# for 30 min, ok. 12-28-10 TDd 8.75 inch pilot hole @ 11100. 12-30-10 Set balanced plug @ 10834 with 270 sx Plugcem H. 12-31-10 Tagged @ 10090 and drilled to KOP @ 10611. 01-01-11 Kicked off 8.75 inch lateral @ 10611. 01-04-11 Set balanced plug @ 10740 with 250 sx Plugcem H. 01-06-11 Tagged @ 10321. Drilled to 10560 and kicked off new 8.75 inch lateral @ 10560. 01-25-11 TDd lateral @ 14811 MD, 10871 TVD.										
14. Thereby certify that the foregoing is	Electronic Submission #19 For CIMAREX ENE	RGY COMPA	NÝ OF CO, sent	to the Hobbs	s	,				
•	E KRUEGER	saling by itol	JRT SIMMONS on 04/12/2011 (11KMS0589SE)  Title REGULATORY ANALYST							
Signature (Electronic S		D 55050 A	Date 04/07/2							
	THIS SPACE FO	H FEDERA	L OH STATE	OFFICE US	5E					
Approved By ACCEPT	ED		JAMES A A TitleSUPERVIS		17		Date 05/01/201			
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the conductive transfer of the conductive trans	itable title to those rights in the		Office Hobbs		(A)	IAY O	4 2011			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #106051 that would not fit on the form

## 32. Additional remarks, continued

02-09-11 Ran 5.5 inch 17# P110 casing. LTC from 0-10006, BTC from 10006-11147, and LTC from 11147-14777. Cmt with lead 935 sx Econocem H, tail 1070 sx Versacem H. 02-10-11 Tested to 5000# for 30 min, ok. RR. TS TOC 1708.