

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBS OCD
MAY 04 2011

WELL API NO. 30-025-24162
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No. 301206
7. Lease Name or Unit Agreement Name Shipp
8. Well Number 004
9. OGRID Number 232611
10. Pool name or Wildcat Humble City; Atoka
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 16' KB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSED DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
SUNDOWN ENERGY LP

3. Address of Operator
13455 NOEL RD, STE. 2000, DALLAS, TX 75240

4. Well Location
Unit Letter I: 1980 feet from the SOUTH line and 660 feet from the EAST line
Section 11 Township 17S Range 37E NMPM LEA County

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/5/2011 MIRU Mayo Marrs PU..
4/6/2011 PU MMCPI tbg, tag @ 9846'
4/8/2011 RIH & start drlg.
4/11/2011 Drill 5' in 5 hrs to 9855'. Got out of csg. RIH down swivel. Start POH.
4/12/2011 RIH & pump 45 sxs "H" cmt @ 9855'. POH. WOC. RIH & tag @ 9739'. Plug depth - 9855-9739'. POH. Spot 25 sxs cmt @ 6450'. Plug depth - 6450-6088'. POH.
4/13/2011 POH. ND BOP. NU WH. Weld on nipple. RIH & cut 4-1/2" csg @ 4850'. Work csg, came free. LD 5 jts.
4/14/2011 POH w/ 78 jts 4-1/2" csg. SDON due to high winds.
4/15/2011 POH w/ 67 jts 4-1/2" csg. RIH & spot 40 sx cmt @ 4900'.
4/18/2011 RIH, tag @ 4735'. Plug depth - 4900-4735'. Pump 40 sxs cmt @ 3100' w/ 2% Cacl2. POH. WOC. RIH, tag @ 2932'. Plug depth - 3100-2932'. POH.
4/19/2011 Pump 40 sxs cmt @ 2000' w/ 2% Cacl2. POH. WOC. RIH, tag @ 1844'. Plug depth - 2000-1844'. POH. Circ 128 sxs cmt f/ 460' to surface. Plug depth - 460' - surface. RDMO PU.
Install marker. Cover cellar. Clean Location. Well P&A'd 4/19/2011.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.

hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Belinda Bradley TITLE Admin. Asst. DATE 5/2/11

Type or print name Belinda Bradley

E-mail address:

Telephone No. 432-943-8770

For State Use Only

APPROVED BY: [Signature] TITLE Staff Mgr DATE 5-5-2011
Conditions of Approval (if any):

Shipp #4

by Jimmy Lewis

432-894-0552

Well P.A'd 4-19-11

1.5 .5 .5
.5 .5 .5
.5 .5 .5

128 sxs plug 460' - surface

13 3/4" 48# w/ 350 sxs set @ 416'
c/c cmt to surface

2.5 .5 .5 .5 .5

40 sxs 2000' - 1844'

2.5 .5 .5 .5 .5
.5 .5 .5 .5 .5

40 sxs plug 3100 - 2932'

40 sxs plug 4900 - 4735'
tagged

2.5 .5 .5 .5 .5
.5 .5 .5 .5 .5

2 5/8" 32# set @ 4800' cmt w/ 150 sxs
Cut + pull 4 1/2" casing @ 4850'

2.5 .5 .5 .5 .5
.5 .5 .5 .5 .5

25 sxs plug 6450 - 6088'

2.5 .5 .5 .5 .5
.5 .5 .5 .5 .5

45 sxs plug 9855 - 9739'

C-BPQ 9888 w/ 52' cmt on top
casing leak 9936 - 10,036'

Est. TOC @ 10,281'

Part 11,662 - 11,672

PBTD 11751
TD 11,785

4 1/2" 9.5# set @ 11,783'
cmt w/ 300 sxs

BOTTOM HOLE PRESSURE
BUILD-UP TESTING
FALL-OFF TESTING
MEMORY GAUGES
SURFACE READOUT

**PRECISION
PRESSURE
DATA, INC.**

SLICKLINE SERVICES
BLANKING PLUGS
PARAFFIN CUTTING
TDS
FISHING

P.O. Box 8571 • Midland, Texas 79708

915-570-7600 • Toll-Free 866-682-4658 • Fax 915-682-3093 • E-mail ppdnc@aol.com