Submit 3 Copies To Appropriate District Office <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 State of New Mexico Energy, Minerals and Natural Resour	rces Form C-103 June 19, 2008
District II OIL CONSERVATION DIVISIO	30-025-30009 V
1301 W. Grand Ave., Artesia, NM 8821 0 District III 1220 South St. Francis Dr.	5. Indicate Type of Lease
1 000 Rio Brazos Rd., Aztec, NM 8741 0 District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	VB-1250
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Palomino State
1. Type of Well: Oil Well 🛛 Gas Well 🗌 Other	8. Well Number 1
2. Name of Operator Mack Energy Corporation	9. OGRID Number / 013837
3. Address of Operator	10. Pool Name or Wildcat
P.O. Box 960 Artesia, NM 88210	Vacuum; Grayburg San Andres
4. Well Location Unit Letter C 330 feet from the North line	1650 and West V
Unit LetterC330feet from theNorthline aSection36Township17SRange351	
Image: Section Social Section 11. Elevation (Show whether DR, RKB, RT,	
3,899' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIALWORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A	
	ICE DRILLING OPNS. P AND A 🛛 🕅
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
5/5/2011 MIRU tagged CIBP @ 3465' Pick up swivel & drilled out plug. RIH to 4600'. Start to POH. 5/9/2011 Circulate hole w/salt gel. Spot 25sx w/ 2% CC WOC. Tag plug @ 4223'. Spot 30sx w/3% CC @ 3480 WOC. Tag plug @	
3241'. Spot 25sx w/3% CC @ 3230' WOC Tag plug @ 2976'. Spot 25sx w/3% CC @ 1958'.	
5/10/2011 Tag cement @ 1680'. Perforate @ 450'. Couldn't break circulation. OCD gave permission to continue plugging. Squeeze	
15sx of cement into the perfs & 65sx of cement to surface. Building Dry Hole Marker.	
Approved for plugging of well hore only.	
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging)	
which may be found at OCD Web Page under Forms, www.cmnrdistate.ttm.us/ocd.	
Spud Date: 1/30/2008 Rig Release Date:	2/21/2008
I hereby certify that the information above is true slid complete to the best of my kn	owledge and belief.
SIGNATURE Cry W. Shenell TITLE Production Clerk DATE 5/11/11	
Type or print name Jerry W. Sherrell E-mail address: jerrys@mec.com PHONE: 575-748-1288	
For State Use Only	
APPROVED BY: TITLE THE DATE 5-12-2011 Conditions of Approval (if any).	
	×