

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
June 19, 2008

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-27828
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <u>Dry Hole</u>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator BOG Resources, Inc.		6. State Oil & Gas Lease No. LG-1145
3. Address of Operator P.O. Box 2267 Midland, TX 79702		7. Lease Name or Unit Agreement Name: Comanche State Unit
4. Well Location Unit Letter H : 1980 feet from the North line and 660 feet from the East line Section 9 Township 21S Range 33E NMPM County Lea		8. Well Number 4
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3840.4' GR		9. OGRID Number 7377
		10. Pool name or Wildcat North Leag (Delaware)

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Set CIBP @ +/- 8620' and cap w/ 35' of cement. * 25sx. cmt. if pumped thru tubing.
2. Cut and pull 5-1/2" casing @ +/- 5950'.
3. Spot 40 sx cement plug at 5-1/2" casing stub. Tag * CIRC. Mud HADEN Fluid, 9.5 BRINE +
4. Spot 60 sx cement plug from 5530' to 5671'. Tag. 12.5 # PBBL. Salt Gel Mud.
5. Spot 40 sx cement plug from 3760' to 3860'. Tag.
6. Spot 40 sx cement plug from 2520' to 2620'. Tag.
7. Pump 195 sx cement plug from 601' to surface.
8. Cut off wellhead and weld on dry hole marker.

Spud Date:

Rig Rel:

The Oil Conservation Division Must be notified
24 hours prior to the beginning of plugging operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 5/12/11

Type or print name Stan Wagner E-mail address: PHONE 432-686-3689

For State Use Only

APPROVED BY Cory W. Hill TITLE DISTRICT 1 SUPERVISOR DATE MAY 18 2011

Conditions of Approval (if any):