			â	Ind Capy 5-23.11
Submit I Copy To Appropriate District Office	State of New Mex Energy, Minerals and Natur			Form C-103 October 13, 2009
District I 1625 N. French Dr., Hobbs, NM 88240		ar resources	WELL API NO.	
District II 1301 W. Grand Ave., Artesia, No. 8210 District III 1000 Rio Brazos Rd., Aztec, NM 87412 5 2011 District IV 1220 S. St. Francis Dr., Santa Fe, NM		30-005-29131 / 5. Indicate Type of Le	ase	
		STATE State Oil & Gas Lea	FEE (
		VO-7395	ise ivo.	
87505 SUNDR VERGENVER AND REPORTS ON WELLS			7. Lease Name or Uni	t Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other		Kruiser BLK State 8. Well Number		
		2		
2. Name of Operator			9. OGRID Number 025575	
Yates Petroleum Corporation 3. Address of Operator		10. Pool name or Wild	dcat	
105 South Fourth Street, Artesia, N	M 88210		Tulk; Wolfcamp, SW	
4. Well Location	1980 feet from the South	line and	2130 feet from the	East line
Unit Letter J : Section 36	Township 15S Ran		NMPM Chaves	County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4166'GR				
	4100	UK		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF IN			SEQUENT REPO	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR				TERING CASING
TEMPORARILY ABANDON				ND A L
DOWNHOLE COMMINGLE	WOETH EE OOM E			
OTHER:		OTHER: 4-1/2" I	iner	\boxtimes
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of				
proposed completion or recompletion.				
2/20/11 - TD 7580'. Drill cement plugs. PU directional tools. Tagged something at 4437'. Picked up swivel and worked through.				
Tagged TOC at 7485'. Dressing off cement.				
2/21/11 – Dress off cement and continue to drill. 2/28/11 – Reached TD 6-1/8" hole to 9790'. Circulated hole clean.				
3/4/11 - Set 4-1/2" 11.6# HCP-110 LT&C liner at 9790'. Hang liner. TOL at 7450'. Float collar at 9711'. Cemented with 305 sx				
Versacem Class "H" cement + 0.4% CFR-3 + 0.5% Halad4-344 + 0.1% Salt (yld 1.22, wt 14.5). NMOCD was notified of intent to cement via voicemail but did not witness.				
			2/4/11	
Spud Date: 4/30/1	Rig Release D	ate:	3/4/11	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
, 1: 1				
SIGNATURE CANAL	furta TITLE Res	gulatory Compliance	e Supervisor DATE	March 17, 2011
Type or print name Tina Hu	ierta E-mail address: <u>t</u>	inah@yatespetroleu	m.com PHONE:	575-748-4168
For State Use Only				
APPROVED BY:	TITLE TITLE	TROLLIAM ENG	DATE_	11941
Conditions of Approval anv):	ν			