Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103	
District I 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		Revised March 25, 1999 WELL API NO.	
District II 1301 W. Grand Avenue, Artesia, NM 88210	OIL CONCEDIATION DIVIGION		30-025-12320	
District III 1220 South St. Francis Dr.		5. Indicate Type of Lease STATE ✓ FEE □		
District IV Santa Fe, NM 87505			Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS			7 I Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:			7. Lease Name or Unit Agreement Name:	
Oil Well Gas Well Other			West Dollarhide Drinkard Unit	
2. Name of Operator Chevron USA Inc			8. Well No. 52	
3. Address of Operator 15 Smith Rd, Midland, TX, 79705			9. Pool name	
4. Well Location				
Unit Letter E:_	1980 feet from the Nor	th line and	660 feet fro	om the West line
Section 32 Township 24-S Range 38-E NMPM Lea County				
10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INT PERFORM REMEDIAL WORK	ENTION TO: PLUG AND ABANDON	SUE REMEDIAL WOR	BSEQUENT RE	EPORT OF: ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR	ILLING OPNS.	PLUG AND
	MULTIPLE COMPLETION	CASING TEST A	ND	ABANDONMENT
OTHER:		OTHER:	•	Replug 🔽
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
 Prior to R/U 13 3/8 csg Drill out cmt from surf to 	had flow and surf well plug i	n 1988 but well repl	lug.	131515151515151515151515151515151515151
 Perf 4 holes at 2400, sqz perfs w/100sx from 2400-2300 (B-Salt) Tag at 2268. Displace hole w/MLF 9.5# Brine w/25# gel P/BBL. 				
5. Perf 4 holes at 1100, unable to sqz, spot 40sx, plug from 1150-1000 (T-Salt).				
6. Perf 4 holes at 650, sqz w/100sx from 650-550 (fresh water) Tag at 498. 7. Perf 4 holes at 368, sqz w/300sx from 368-300 (13 3/8 Shoe) Tag at 290.				
8. Perf 4 holes at 290, sqz w/100sx from 290-250, Tag at 236.				
9. Perf 4 holes at 230, circ cmt 7" x 9 5/8 csg w/90sx, Tag at 62. 10. Fill 7" csg w/cmt from 62-Surf w/15sx. Install dry hole markApprosed4as to plugging of the Well Bore. 11. Fill 7" csg w/cmt from 62-Surf w/15sx. Install dry hole markApprosed4as to plugging of the Well Bore.				
Liability under bond is retained until surface restoration is completed.				
		Stifface rest		
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE	TITL	Manager/Sun	set	DATE_2/18/04
Type or print name Jimmy Bagley Telephone No. (432) 561-8600				
(This space for State use) OC FIELD REPRESENTATIVE II/STAFF MANAGER				
APPPROVED BY ACULTY TITLE DATE:				
Conditions of approval, if any: MAR 2 3 2004				
	,			

%