

AREA 640 ACRES  
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

National Cooperative Refinery Ass'n.

P.O. Box 1231, Wichita, Kansas

Skarda

Company or Operator

Well No. 1

in

C

of Sec. 3

T. 2 N

Lease

R. . . . ., N. M. P. M. . . . . Field, . . . . . County.

Well is 490 feet south of the North line and 491 feet west of the East line of SE/4

If State land the oil and gas lease is No. . . . . Assignment No. . . . .

If patented land the owner is . . . . . Address . . . . .

If Government land the permittee is . . . . . Address . . . . .

The Lessee is C &amp; B Oil Company Address Dallas, Texas

Drilling commenced April 15 19 48 Drilling was completed June 11 19 48

Name of drilling contractor Western Drilling Company Address . . . . .

Elevation above sea level at top of casing 4421 feet.

The information given is to be kept confidential until . . . . . 19 . . . . .

## OIL SANDS OR ZONES

No. 1, from 3080 to 3425 No. 4, from - to -

No. 2, from 3500 to 3540 No. 5, from - to -

No. 3, from - to - No. 6, from - to -

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from - to Rotary feet. -

No. 2, from - to - feet. -

No. 3, from - to - feet. -

No. 4, from - to - feet. -

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10-3/4"	40	8	?	197'	Corn	-	-	-	Surface
5-1/2"	14	8	?	3500'	Float	-	-	-	Oil String

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15	10-3/4	197'	50	Plug	?	?
8-3/4	5-1/2	3500'	200	Plug	?	?

## PLUGS AND ADAPTERS

Heaving plug—Material . . . . . Length . . . . . Depth Set . . . . .

Adapters — Material . . . . . Size . . . . .

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
-	-	Acid	14,000	10-24	3080-3425	T.D.

Results of shooting or chemical treatment No Results

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 3800 feet, and from - feet to - feet

Cable tools were used from - feet to - feet, and from - feet to - feet

## PRODUCTION

Put to producing - 19 . . . . .

The production of the first 24 hours was - barrels of fluid of which - % was oil; - %

emulsion; 100 % water; and - % sediment. Gravity, Be. -

If gas well, cu. ft. per 24 hours. - Gallons gasoline per 1,000 cu. ft. of gas. -

Rock pressure, lbs. per sq. in. -

## EMPLOYEES

E. R. Selby

Driller

Geo. Kiffmeyer

Driller

Driller

Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9th

day of November, 19 48

Mabel Tally

Notary Public

My Commission expires Feb. 11, 1950

Wichita, Kas

Place

11/9/48

Date

Name Tom Hamilton

Position Engineer

Representing Natl Coop Ref Ass'n

Company or Operator

Address O Box 1231

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	40		Galochi
40	60		Shell
60	193		Sand and Andy
193	508		" " Shale
508	797		" " "
797	1163		Red Bed and Sand
1163	1707		Sand and Shale
1707	2277		Lime Shells & Sand, Andy
2277	2515		Lime and Shale
2515	2612		Lime
2612	2657		Hard Lime and Andy
2657	2693		Lime
2693	2735		Andy
2735	2837		Sandy Shale & Lime
2837	3095		Lime and Andy
3095	3128		Brown Sand - Show Oil - Gas Core #1 3110 to 3128
3128	3262		Lime Sand and Shale
3262	3285		Lime and Sand
3285	3300		Shale and Lime
3300	3425		Lime and Sand
3425	3647		Red Shale
3647	3800		Shale and Sand
Ran 197' 10-3/4" Casing Cemented 50 sacks			
Ran 3493.11' 5-1/2" O.D. Casing - Cemented w/100 sacks			