

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Cities Service Oil Company		5. State Oil & Gas Lease No.
3. Address of Operator Box 4906 - Midland, Texas 79701		7. Unit Agreement Name
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 3N RANGE 31E NMPM.		8. Farm or Lease Name Swink A
15. Elevation (Show whether DF, RT, GR, etc.) 4544' GR		9. Well No. 1
12. County Curry		10. Field and Pool, or Wildcat Wildcat

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOBS ☐
 OTHER ☐
 ALTERING CASING ☐
 PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 7346' Granite Wash. Plugged and abandoned. This well was plugged and abandoned in the following manner:

1. Loaded hole with mud laden fluid.
2. Displaced a 50 sack cement plug @ T.D. 7346-7196'.
3. Displaced a 50 sack cement plug @ 5953-5803'.
4. Displaced a 50 sack cement plug @ 5126-4970'.
5. Displaced a 50 sack cement plug @ 3967-3817'.
6. Displaced a 50 sack cement plug @ 2082-1932'.
7. Displaced a 50 sack cement plug @ 1319-1169'. (1/2 in and 1/2 out of 9-5/8" casing set and cemented @ 1233').
8. Spotted a 10 sack cement surface plug @ 30-0' with a 4" dry hole marker extended 4' above ground level to designate a plugged and abandoned location.
9. Location has been cleared of all equipment and debris and is ready for final inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Espey TITLE Region Operation Manager DATE April 27, 1973

APPROVED BY John W. Runyan TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: