



NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE OCC
Santa Fe, New Mexico

1961 JUL 3 AM 5:41
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

FRANKLIN, ASTON & FAIR, INC.

Green Estate

(Company or Operator)

(Lease)

Well No. **1**, in **SW** $\frac{1}{4}$ of **SW** $\frac{1}{4}$ of Sec. **10**, T. **5 North**, R. **32 East**, NMPM.

Undesignated

Curry

Well is **660** feet from **West** line and **1980** feet from **South** line

of Section **10**. If State Land the Oil and Gas Lease No. is

Drilling Commenced **May 13, 1961** Drilling was Completed **June 27, 1961**

Name of Drilling Contractor **Lee Drilling Company**

Address **Philtower Building, Tulsa, Oklahoma**

Elevation above sea level at Top of Tubing Head **4635.07'** The information given is to be kept confidential until
19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **900** to **1270** feet. **Santa Rosa**

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

| SIZE | WEIGHT PER FOOT | NEW OR USED | AMOUNT | KIND OF SHOE | CUT AND PULLED FROM | PERFORATIONS | PURPOSE |
|---------------|-----------------|-----------------|--------------|------------------------------|---------------------|--------------|---------|
| 13 3/8 | | New | 268' | Set w/280 sax poe mix | | | |
| 8 5/8 | 24 J-55 | New | | | | | |
| | | Seamless | 2615' | | | | |

MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. BAGS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|--------------|--|-------------|-------------|--------------------|
| | 13 3/8 | 268' | 280 sax poe mix circulated to surface | | | |
| | 8 5/8 | 2615' | 300 sax poe mix, 200 sax liner bent circulated to surface | | | |

RECORD OF PRODUCTION AND STIMULATION PLUGGING PROCEDURE

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Well plugged as follows: **June 29, 1961 - 20 sax cement at 8181 TD. 20 sax Top Pennsylvanian - 6900 - 6835'. 20 sax bottom of 8 5/8 casing - 2618 - 2555'. 10 sax 32' to surface.**

The above plugging procedure recommended by Engineering Department of New Mexico Oil Conservation Commission, Hobbs, New Mexico

Result of Production Stimulation

Depth Cleaned Out

2

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to TD 8181 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing....., 19.....

OIL WELL: The production during the first 24 hours wasbarrels of liquid of which% was
was oil;% was emulsion;% water; and% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

| | | |
|--------------------|---------------------|----------------------------|
| T. Anhy..... | T. Devonian..... | T. Ojo Alamo..... |
| T. Salt..... | T. Silurian..... | T. Kirtland-Fruitland..... |
| B. Salt..... | T. Montoya..... | T. Farmington..... |
| T. Yates..... | T. Simpson..... | T. Pictured Cliffs..... |
| T. 7 Rivers..... | T. McKee..... | T. Menefee..... |
| T. Queen..... | T. Ellenburger..... | T. Point Lookout..... |
| T. Grayburg..... | T. Gr. Wash..... | T. Mancos..... |
| T. San Andres..... | T. Granite..... | T. Dakota..... |
| T. Glorieta..... | T. | T. Morrison..... |
| T. Drinkard..... | T. | T. Penn..... |
| T. Tubbs..... | T. | T. |
| T. Abo..... | T. | T. |
| T. Penn..... | T. | T. |
| T. Miss..... | T. | T. |

FORMATION RECORD

| From | To | Thickness in Feet | Formation | From | To | Thickness in Feet | Formation |
|------|------|----------------------|------------------------|------|----|----------------------|-----------|
| 1270 | 1445 | 175 | Anhydrite | | | | |
| 2237 | 4850 | 2613 | San Andres | | | | |
| 4850 | 6196 | 1346 | Abo | | | | |
| 6196 | 6894 | 698 | Wolfcamp | | | | |
| 6894 | 8174 | 1280 | Pennsylvanian | | | | |
| 8174 | | | Granite (Pre Cambrian) | | | | |

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 30, 1961

.....
(Date)

Company or Operator.....**FRANKLIN, ASTON & FAIR, INC.**

Address P. O. Box 1090, Roswell, New Mexico

Name B. R. Anand

Position or Title **Vice President**