

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES

June 9 2 55 PM '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the person on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the:

O. C. Stevens

(Company or Operator)

Well No. **1** in **I** (Unit)

NE 1/4 SE 1/4 of Sec. **5**, T. **2 N**, R. **31 E**, NMPM., **Wildcat** Pool
(40-acre Subdivision)
Curry County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Prepared to plug: **June 4, 1964**

4 sacks cement with 4% calcium chloride by dump bailer-plug from 3011 to 2970 in 4 1/2" casing.

Baker cast iron casing plug set at 2906' in 4 1/2" casing.

Baker cast iron casing plug set at 2374' in 4 1/2" casing.

Shoot 4 1/2" casing off at 2206 and place following plugs by pump truck while pulling casing:--10.8ppg mud laden fluid placed from 2374 to 2206'.

25 sacks cement-plug from 2206 to 2118, then place 10.8ppg mud laden fluid to 1410'.

25 sacks cement-plug from 1410 to 1322, then place 10.8ppg. mud laden fluid to 503'.

25 sacks cement--plug from 503 to 420', in and out of 3 5/8" casing, then place 10.8ppg. mud laden fluid to 33'

10 sacks cement-plug from 33 to 0'.

Approved: _____, 19____
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By: _____

Title: _____

O. C. Stevens

Company or Operator

By: _____

Position: **Supt.**

Send Communications regarding well to:

Name: **J. H. Everitt**

Address: **Route 1, Box 186-0**

Hansfield, Texas 76063