DREICE OIL			~.			. نگر		بعب	E			
FE OHEICE	D				(Bertaul T	Sh.						
DE EICE			المنطقة المعمومون	and and a second		MT		See	tic	n 2		
OIL				CONSERVAT		SION						
TION OFFICE			AR 3 1 26	ta Fe, New Me	KiCO							
TOR		<b>=</b>   '	16.33			<u></u>	1		7			
			WE	LL RECO	RD	-	-			_		
		Sec. September 1			· .		-	X	一†	-+		
later than tw	venty days a	fter completion		, to which Form instructions in R If State Land	ules and Regulat	ions '-	Loc	ARI	EA 64 WELI	0 ACR	ES RECTLY	
	Shell Of	Company			0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Stephe	naon.	••••••				•••••
ell No	1	in NE	¼ of <b>S</b> ₩	.¼, of Sec	<b>2</b> T	3-N		R	32-	·Ε	NM	РM
	•		=	Pool,								
				line and	_							
			-	nd Gas Lesse No.								
				Ţ								
				19 Drilling								
me of <b>Drilling</b>	Contractor.	Forst	er Drilling	Company - 1	lox 32 - 0d	issa,I	exas.	•••••	*****		**********	•••••
. 2, from		to		No. 4	from		t	o	· • • • • • · ·			•••••
. 1, from	6500		evation to which	BTANT WATER water rose in hole6750	·····			•			OST Inf	
. 3, from			to	····		.feet		•••••	·····		*** **********	•••••
. 4, from			to	***************************************	***************************************	.feet	·········		••••••	· • • • • • • • • • • • • • • • • •	**************	•
				CASING RECO	RD							
	WEIGHT	NEW OR		KIND OF	CUT AND	<del> </del>	<del></del> .	<del></del>			<del></del>	-
	PER FOOT	USED	AMOUNT	SHOE	PULLED FROM	PERFO	RATION	8		PU	RPOSE	
SIZE			4541								ce str	
3 3/8"	484	Neu	2444							ECH	rdiate	st
3 3/8"	48# 32#	Nev	3103'						LRU			
3 3/8"			3103'						LRI			
3 3/8"				AND CHIMENE	NG RECORD				Lat			
3 3/8" 8 5/8"	32#		MUDDING	AND CEMENT		MUD				40UNT	oF	
3 3/8" 8 5/8" SIZE OF CA	32#	Nev		AND CEMENT	a	RAVITY			AM M	fount UD Us	OF SED	
3 3/8" 8 5/8"  SIZE OF SE CZ 7 1/2 13	32# ZE OF ABING 3/8"	WHERE SET	MUDDING NO. SACKS OF CRIMENT	METHOD USED	a	MUD RAVITY	urfe		AM M	40UNT UD U	OF SED	
3 3/8" 8 5/8"  SIZE OF SE CZ	32#	WHERE	MUDDING NO. SACKS OF CRIMENT	METHOD USED	a	RAVITY	wfec	:e	AM M	40UNT UD US	OF	
3 3/8" 8 5/8"  SIZE OF SE CZ	32# ZE OF ABING 3/8"	WHERE SET	MUDDING NO. SACKS OF CRIMENT	METHOD USED	a	RAVITY	wfec	`e	AM M	40UNT UD US	OF	
3 3/8" 8 5/8"  SIZE OF SE CZ	32# ZE OF ABING 3/8"	WHERE SET	MUDDING NO. SACKS OF CEMENT 475 2200	METHOD USED	Cement	ed to S	urfac	·e	AM M	40UNT UD U	OF	
3 3/8" 8 5/8"  SIZE OF SE CZ	32# ZE OF ABING 3/8"	WHERE SET 464' 3115'	MUDDING NO. SACES OF CEMENT 475 2200 RECORD OF	Pump & Plug Pump & Plug Pump & Plug Pump & Plug	Cement:	ravity  ed to S			AM M	40UNT UD U	OF	
3 3/8" 8 5/8"  SIZE OF SE CZ	32# ZE OF ABING 3/8"	WHERE SET 464' 3115'	MUDDING NO. SACES OF CEMENT 475 2200 RECORD OF	Pump & Plug Pump & Plug Pump & Plug PRODUCTION A o. of Qu. or Gal	Cement	ION	shot.)		AM			
3 3/8" 8 5/8"  SIZE OF SE CZ	32# ZE OF ABING 3/8"	WHERE SET 464' 3115'	MUDDING NO. SACES OF CEMENT 475 2200 RECORD OF	Pump & Plug Pump & Plug Pump & Plug PRODUCTION A o. of Qu. or Gal	Cement:	ION	shot.)		AM			
3 3/8" 8 5/8"  SIZE OF SI CZ 7 1/2" 13	32# ZE OF ASING 3/8" 5/8"	WHERE SET 464 3115 (Record the	MUDDING NO. SACES OF CEMENT 475 2200  RECORD OF Process used, N	Pump & Plug Pump & Plug Pump & Plug PRODUCTION A o. of Qu. or Gal	Cement:  Coment:	ION	shot.)		AM			

Depth Cleaned Out.....

Result of Production Stimulation.....

## SOORD OF DRILL-STEM AND SPECIAL T.

If drill-stem or other special tests or dexiation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

	, were (	sed from	PAGE	feet to		nd from		feet to	fec				
				PRODU									
Put to P	roducing.		P&A, Feb. 2	2									
OIL WE	LL: T	he producti	on during the first	24 hours was	**************	ba	rrels of liq	uid of which	% w				
•				was emulsion;									
						70 ***	• ,	······································	scamicut, A.F.				
GAS WE							_						
0110 112				24 hours was	*************	м,С.Г. р	lus		barrels				
				essurclbs.					•				
				·······									
PLE	ASE IN	DICATE E	ELOW FORMA Southeastern	TION TOPS (IN CON	FORMAN	CE WIT	H GEOGE						
T. Anhy	<b>7</b>		Svatnesstern .				Т.	Northwestern New					
			,										
			*****************	T. Montoya				Farmington					
			7 <b>700</b> 00 - 700 6 700 6 700 700 700 700 700 700 700					Pictured Cliffs					
			***************************************	1/				Menefee					
								Point Lookout					
r. San A	Andres	2222' (	+2346')	T. Granite 69	7			Dakota					
Γ. Glori	cta			T. Base Red B	eda150	4! (±30		Morrison					
			<del>(-152')</del>					Penn					
			<u> </u>					***************************************					
			1		-								
			•••••			-			***************************************				
								***************************************					
			,	FORMATIO:	n reco	RD		***************************************	•				
From	То	Thickness in Feet	Fe	FORMATIO	N RECC	To	Thickness in Feet		ion				
		in Feet	F				Thickness		ion				
rface	1504	in Feet	Red Beds	ormation			Thickness		ion				
rface		in Feet	Red Beds Shale, Sal	ormation			Thickness		ion				
rface 504 500	1504 2500 5223	1504 996 2723	Red Beds Shale, Sal Dolomite w Siltston	t, & Siltstone /selt, Shele &			Thickness		ion				
rface 104 100	1504 2500 5223 6005	1504 996 2723 782	Red Beds Shale, Sal Dolomite w Siltston Red Shale	t, & Siltstone /selt, Shale & &			Thickness		ion				
rface 604 600 223	1504 2500 5223	1504 996 2723	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w	t, & Siltstone /selt, Shale & &			Thickness		ion				
rface 604 600 123 105 600	1504 2500 5223 6005 6500 6854	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone w Shale	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
rface i04 i00 23 05 i00	1504 2500 5223 6005 6500	1504 996 2723 782 495	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
rface 504 500 223 505 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
rface 504 500 223 505 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
irface 504 500 223 505 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
From  arface 504 500 223 005 500 354	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
urface 504 500 223 005 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
urface 504 500 223 005 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
irface 504 500 223 505 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
urface 504 500 223 005 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				
urface 504 500 223 005 500	1504 2500 5223 6005 6500 6854 6900	1504 996 2723 782 495 294	Red Beds Shale, Sal Dolomite w Siltston Red Shale Limestone Dolomite w Shale Granite Wa	t, & Siltstone /salt, Shale & & & Siltstone w/Shale /Limestone &			Thickness		ion				

## ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

1 1	nereby swear	or amrm	that the	e information	given	herewith	18 4	complete	and	correct	record	of	the '	well	and	all w	vork (	done :	on it	10	far
as can	be determined	from av	ailable r	records.																	
											_	_									

Company or Operator.....Shell Oil Company

Address P. O. Box 1858; Roswell, New Mexico

R. A. LOWED.