

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R124.

5. LEASE DESIGNATION AND SERIAL

LC-069966

6. IF INDIAN, ALLOTMENT OR TRUST

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Eugene E. Nearburg

3. ADDRESS OF OPERATOR

3303 Lee Parkway Dallas, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

760' FSL & 760' FEL Sec. 19

SE SE-19-8-37 NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, WT, GR, etc.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Saikin

9. WELL NO.

#3

10. FIELD AND POOL, OR WILDCAT

Bluitt, Penn
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

19-8-37

12. COUNTY OR PARISH 13. STATE

Roosevelt NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. Will spot a 20 sx plug in bottom to cover all perforations.
2. Will spot a 25 sx plug at stub of 4 1/2" casing.
3. Will spot a 25 sx plug at shoe of 7 5/8" casing.
4. Will spot a 25 sx plug at stub of 7 5/8" casing.
5. Will spot a 25 sx plug at shoe of 11 3/4" casing.
6. Will spot a 10 sx plug at top and erect a regulation marker.
7. Will load hole with mud.

AMENDMENT:

If 4 1/2" casing is pulled below base of San Andres, spot additional
25 sack plug at base of San Andres 5400-5500'.

18. I hereby certify that the foregoing is true and correct.

SIGNED

Hobbs, Pipes & Supply
[Signature]

TITLE Asst. Mgr.

DATE 8-21-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

AUG 29 1967

A. R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side