## YATES PETROLEUM CORPORATION

Dwight "AZI" State Com #1 Re-entry 660' FSL & 660' FEL Section 15-T9S-R32E Lea County, New Mexico Lease #VA-2165

Drilling Plans: Yates Petroleum Corporation plans to re-enter this well bore using a pulling unit and a reverse unit to drill out the cement plugs in the 13 3/8" casing and the 11" open hole to the top of the 8 5/8" casing stub. The 8 5/8" casing will be repaired and tied back to surface and cement circulated. After the 8 5/8" casing has been repaired the cement plugs in the 8 5/8" casing and the 7 7/8" open hole will be drilled out to the top of the 5  $\frac{1}{2}$ " casing stub at 6600'. The 5  $\frac{1}{2}$ " casing will be repaired and tied back to surface and cemented back to approximately 3000'. After the 5  $\frac{1}{2}$ " casing has been repaired the cement plugs inside the 5  $\frac{1}{2}$ " casing will be cleaned out to a TD of 10,965'. The mud program to be used will be 9.2-9.5 ppg brine water with a 55-70 cp viscosity. A 5000# BOPE will be installed on the 8 5/8" casing.

The well will be completed using a pulling unit. The well will be completed and tested in an Atoka sand zone in the interval from 10,100' to 10,400'.