

State of New Mexico  
Energy, Minerals and Natural Resources Department

DISTRICT I  
P.O. Box 1980, Hobbs NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia NM 88210

1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088

WELL APN NO.	
30-025-00005	
State	<input checked="" type="checkbox"/> FEE
6. State Oil & Gas Lease No.	
VA-2165	
7. Lease Name or Unit Agreement Name	
Dwight AZI State Com	
8. Well No.	
2	
9. Pool Name or Wildcat	
S.R.R. Atoka Gas	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 105 South 4th, Artesia, NM 88210	4. Well Location Unit Letter J : 1980 Feet From The South Line and 1980 Feet From The East Line Section 15 Township 9S Range 32E NMPM Lea COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4346' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:  
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

SUBSEQUENT REPORT OF:  
REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER Re-Entry Operations ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud on surface plug 8-10-01. Drilled cement. Drained csg and found dry hole marker in csg. Made up 12-1/4" shoe on 4-3/4" DC. Cut 4' core. Had all of marker, drill 5' cmt. Fell out. Wash down to 168'. Returns coming up in cellar around 13-3/8". RU vacuum truck and pulled fluid from inside 13-3/8". Saw half dollar size hole 2-3' below cellar btm. Ran 2 jts 2-3/8" tbg and pump 100 sx "C" neat w/3% CaCl. Circulated out hole into cellar. Drilled to 810'. Pulled collar log. Showed bad spots @ 770', 680', and 480'. TIH w/caliper. Could not read wall thickness. Indicates outside pipe. TIH w/spear and grapple. Pulled 70K. Release spear and TOH. Grapple sprung like beside or below a collar. Drilled to 872' and TOH. TIH w/fish finder. Indicates outside pipe. Found cut in 8-5/8" csg @ 760', 670', 590', 470'. RD. Mix and pump 225 sx Class C w/2% CaCl. WOC 2 hrs. Tag @ 290'. Pull up and spot 25 sx plug @ surface. Cut off 13-3/8" head. Install dry hole marker. P&A 8-21-01. FINAL REPORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 7/3/02  
TYPE OR PRINT NAME Stormi Davis TELEPHONE NO 505-748-1471

(This space for State Use)  
APPROVED BY Billy E. Pugh TITLE COMPLIANCE OFFICER DATE AUG 07 2002  
CONDITIONS OF APPROVAL, IF ANY:

EC

Kz GWN

8