

LOG OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 10,577 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing May 11, 1956

OIL WELL: The production during the first 24 hours was 23.27 barrels of liquid of which 95.05 % was after load recovered
was oil; % was emulsion; 4.95 % water; and % was sediment. A.P.I.

Gravity 42.3 corrected

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1623'	T. Dromedary Miss.	10430'
T. Salt	1687'	T. Sundar Miss. Chert	10528'
B. Salt	2180'	T. Montoya	
T. Yates	2260'	T. Simpson	
XXXXXX B. Yates	2377'	T. McKee	
T. Queen	2926'	T. Ellenburger	
T. Gray San Andres	3472'	T. Gr. Wash	
T. B. San Andres	4860'	T. Granite	
T. Clearfork Paddock	5170'	T.	
T. Clearfork Clearfork	5632'	T.	
T. Tubbs	6330'	T.	
T. Abo	7177'	T.	
T. Wolf Wolfcamp	8204'	T.	
T. Penn. Penn.	8530'	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	6	6	Cellar				
6	1623	1617	Red Bed				
1623	1687	64	Anhydrite				
1687	2180	493	Anhydrite, salt & shale				
2180	2260	80	Anhydrite				
2260	2377	117	Sand & shale				
2377	3472	1095	Sand, Shale, salt & Anhydrite				
3472	4860	1388	Anhydrite, Dolomite & Lime				
4860	5170	310	Dolomite, Anhydrite & Sand				
5170	5220	50	Dolomite				
5220	5632	412	Dolomite, Sand, Shale & Anhydrite				
5632	6330	698	Dolomite, Sand, Shale & Anhydrite w/ salt stringers				
6330	6500	170	Sand & Shale				
6500	7177	677	Dolomite and Anhydrite				
7177	7700	523	Shale w/ Dolomite stringers				
7700	8204	504	Dolomite & Anhydrite				
8204	8350	146	Dolomite, Chert & Shale				
8350	10000	1650	Lime, Shale w/ Chert stringers				
10000	10430	430	Lime, Shale & Sand				
10430	10528	98	Lime				
10528	10577	49	Lime & Chert				
	10577		Total Depth				
	10436		Drilled out Depth				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 11, 1956

(Date)

Company or Operator Amerada Petr. Corp. Address Roswell Star Route - Tatum, New Mex.
Name H. H. Lissman Position or Title Foreman