

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Test Csg. Shut-off X		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

October 16, 1952
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State "AD"

Cities Production Corporation
(Company or Operator)

Well No. **1** in **0**
(Unit)

C-SW $\frac{1}{4}$ **SE** $\frac{1}{4}$ of Sec. **22**, T. **10-S**, R. **32-E**, NMPM., **Undesignated** Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to a total depth of 9910' in lime. Ran 248 1/2 joints of 5 1/2" OD 15.5#, 17# and 20# casing, 9898.2 set at 9910' with Halliburton multiple stage cementing DV collar at 9572'. Cemented first stage with 90 sacks of cement mixed with 6% gel and 1/4# Flocele per sack. Circulated out an excess of 5 sacks above DV collar. Circulated 8 hours and cemented with second stage consisting of 50 sacks strata crete and 800 sacks cement with 6% gel. Plug-down at 8:30 P.M. October 15, 1952. Cement will be allowed to set 48 hours before testing for shut-off.

Approved..... **OCT 23 1952**, 19.....
Except as follows:

Cities Production Corporation
Company or Operator

By..... *[Signature]*

Position..... **District Superintendent**

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By..... *[Signature]*

Title..... **Oil & Gas Inspector**

Name..... **E. M. Ely**

Address..... **Box 97, Hobbs, New Mexico**