	*		(Form C-103) (Revised 7/1/52)
the second s		Dra	
NEW MEXICO OIL CONSERVATION C	COMMISSIO	N IIIA	
Santa Fe, New Mexico		1 41562	200
	1	- 4:	W/2
MISCELLANEOUS REPORTS	ON WER	Real MAN	×8707
MISUELLANEOUS REPORTS		-OMSFOR ~9	100 11/1
a state of the second of the s	ission within 1	Nate after the wor	k specified is com-
Submit this report in TRIPLICATE to the District Office, Oil Conservation Commis cted. It should be signed and filed as a report on Beginning Drilling Operations, Results	sof test of casi	ng shin die result/	a alugging of well.
cted. It should be signed and filed as a report on beginning Drining Operations, Result	and hy an am	ant of the Commiss	in JStr. additional

pleted. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shures result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	x	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)

June 26, 1953	Hobbs,	
(Date)		 (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Production Corporation	State "ADH				
(Company or Operator)	(Lease)				
Guy Mabee Drilling Company	Nell No	····,			
(Contractor) T. 10-S. R. 32-E. NMPM, Mescalero-Devonian		ty.			
The Dates of this work were as folows: February 2 & 3, 1953					
Notice of intention to do the work (was) (seasoner) submitted on Form	-102 on	53			

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

State "AD" #2 was drilled to a total depth of 10,491' in line. 13 3/8" OD 48# H-40 SS Casing was set at 392' and left in the hole, cement circulated. 8 5/8" OD 24# & 32# Casing was set at 3540' and left in hole, cement circulated. The hole was loaded with approximately 650 bbls of 10.4 mud laden fluid. Four plugs, consisting of 50 sacks of cement each, were spotted at 10,331' to 10,491', 8640' to 8800', 8190' to 8350', 3575' to 3415' respectively, each plug being approximately 160' in length. An additional 10' plug was placed in the top of 8 5/8" casing. A 4" pipe marker has been installed to mark the abandoned location. The pits have been filled and leveled and location cleared of junk.

Wm. McDonald, Tool Pusher for Guy Mabee Drilling Company, Odessa, Texas, W. M. Dickey, Production Foreman, Cities Service Oil Company, Hobbs, New Mexico were in charge of the work.

Witnessed byC. M. Hartwell (Name)	Cities Ser	(Company)	District Superintendent
Approved: OIL CONSERVATION COMMISSION Muthraugh (Name) (True) (True) (True)	•	NameDistri Position	information given above is true and complete dge. M. Hull ct Superintendent Service Gil Co. pany , Hobbs, New Mexico

t set set set set set of the set 1

n MMMAR – Standing Berger Standing Standin Standing Stan Standing Standing