

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Templo	
9. Well No. 1	
10. Field and Pool, or Wildcat Undesignated	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER - Dry Hole

2. Name of Operator
Britton Management Corporation

3. Address of Operator
Britton Oil Building, 312 N. Big Spring, Midland, Texas 79701

4. Location of Well
UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 34 TOWNSHIP 10-S RANGE 32-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Top of fish @ 7256'. Spotted 40 sacks cement from 7256' to 6967'. Cut 5 1/2" csg at 5075' and recovered same. Spotted 40 sack plug 5124' to 5014'. Spotted 40 sack plug at top of Glorieta 4790' to 4890'. Spotted 45 sack plug 3485' to 3585' (bottom of 9 5/8" csg @ 3531'). Spotted 45 sack plug opposite salt at 1645' to 1745'. Spotted 10 sack plug from surface to 25'. Cut off wellhead and welded plate and marker on 9 5/8" csg. Plugging completed 4/3/79. This procedure was approved verbally by the Commission on 3/22/79.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. J. Evans TITLE Manager DATE 4/4/79

APPROVED BY Edwin W. Sney TITLE OIL & GAS INSPECTOR DATE AUG 16 1979

CONDITIONS OF APPROVAL, IF ANY: