

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED

AUG 25 1952

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

|   |          |   |  |                          |  |
|---|----------|---|--|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS |          | REPORT ON RESULT OF TEST OF CASING SHUT-OFF |  | REPORT ON REPAIRING WELL |  |
| REPORT ON RESULT OF PLUGGING WELL       | <b>X</b> | REPORT ON RECOMPLETION OPERATION            |  | REPORT ON (Other)        |  |

August 23, 1952

(Date)

Monument, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

State M\*B\*

(Lease)

Noble Drilling Corporation

(Contractor)

Well No. 1 in the C/SW/4 SE/4 of Sec. 11

T 11-S, R 32-E, NMPM, Wildcat Pool, Lea County.

The Dates of this work were as follows: August 19, 1952

Notice of intention to do the work (was) (~~received~~ submitted on Form C-102 on August 18, 1952, 19

(Cross out incorrect words)

and approval of the proposed plan (was) (~~received~~ obtained).

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11060' Total Depth - 8825' Plug Back Depth. 8421' Drilled out Depth -

Filled hole with heavy mud from 8421' to 3485' - spotted cement plug from 3485' to 3370' with 35 sacks cement. Filled hole with heavy mud from 3370' to 1475' and spotted cement plug from 1475' to 1400' with 25 sacks cement. Filled with mud from 1400' to 300' and spotted cement plug from 300' to 240' with 50 sacks cement. Spotted 10 sacks cement in top of 13-3/8" OD csg. and set a piece of 4" line pipe to extend 5' above ground level as marker - Well plugged and abandoned 8/19/52 -

Witnessed by E. A. Buchanan

(Name)

Amerada Petroleum Corporation

(Company)

Farm Boss -

(Title)

Approved:

OIL CONSERVATION COMMISSION

Roy Yarbrough

(Name)

Oil &amp; Gas Engineer

(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation

Address Drawer D, Monument, New Mexico

AUG 25 1952

(Date)