

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in **TRIPPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 27, 1953
(Date)

Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

Coleman W. Robinson "A"
(Lease)

McVay & Stafford Drlg. Company
(Contractor)

Well No. 1 in the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 14

T. 11-S, R. 32-E, NMPM., Moore - Devonian Pool, Lea County.

The Dates of this work were as follows: March 26, 1953

Notice of intention to do the work (~~was~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,660' Total Depth Line. Finished drilling 7-7/8" hole @ 12:22 PM, 3/23/53. Ran Schlumberger surveys. Ran a total of 302 joints 5-1/2" OD casing set @ 10,565' and cemented w/ 600 sacks cement. Pumped plug to 10,484' @ 1:40 AM on 3/23/53. Max. Pump Press. - 1600#. Ran temperature survey - top of cement outside of 5-1/2" casing at 7517', or 73.6% Fill. After WBS for 24 hours tested 5-1/2" casing for 1/2 hour with 1000# - No pressure drop. Drilled cement from 10,484' to 10,565' and washed from 10,565' to 10,660'. Open hole from 10,565' to 10,660'. Tested 5-1/2" casing with 1000# for 1/2 hour after drilling cement plug - no pressure drop. Continued with completion operations.

Witnessed by R. J. Brakey
(Name)

Amerada Petroleum Corporation
(Company)

Farm Boss
(Title)

Approved: OIL CONSERVATION COMMISSION

Roy Yarbrough
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name C. W. Robinson

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation

Address Reeswell Star Route Tatum, New Mex.

1908 Aug 9 9311