ي <del>ج</del> ديني		-1	DECE	PIWE	nC-103) //1/52)
NEW MEXICO	OIL CONSERVATION	COMMIS			
	Santa Fe, New Mexico		SEP	8 1953	
MISCELLAN	IEOUS REPORTS	ON W	BIL CONSERVI	ATION COMMISSION	

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corperation	Coleman W. J	Robinson "A"	
(Company or Operator)		(Lease)	
KeVay & Stafford Drilling Co., Inc.	Well No. 3in t	he <b>C/SI</b> 1/4 SE 1/4 of	Sec,
T. 11-5, R. 32-E, NMPM., Moore - Devonian	Pool,	Lea	County.
The Dates of this work were as folows: September 2, 1953			
Notice of intention to do the work (was) (parage) submitted on Form	G-102 on Sept.	. 1	19 53
rionee of intention to do the norm (was) ( ) addition of a office		and incoment monday	·····, ····,

~~~~ (Cross out incorrect words)

and approval of the proposed plan (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,715' Total Depth. Line. Finished drilling 7-7/8" hole @ 1:14 PM on 8/31/53. Ran drill stem test from 10,700' to 10,715' - four hour test - no gas or fluid to surface. Recovered 1605' of water blanket and 2598' of salt and sulphur water. No show of oil or gas. Prepared to plug and abandon. Hole was filled with heavy drilling mad. Spotted a 35 sack coment plug from 10.601 to 10.715 and a 35 sack commt plug from \$500' to 8414's a 35 suck ement plug from 3455! to 3572'. Ran Dia-log easing cutter and cut off 8-5/8" OD casing @ 1058". Salvaged 1045" of 8-5/8" OD casing. Filled hole with drilling mad and spotted 10 sack comment plug from 298' to 306' and a 10 sack commont plug in top of 13-3/8" OD casing from 6 to 10". A piece of 4" line pipe was comented in top of 13-3/8" OD sasing and extends five feet above ground level to serve as a marker. Well plugged and abandoned on September 2, 1953.

| Witnessed byBaymond Q. Swanaon (Name)   | Amerada Pe | (Company)                                                     | Farm Boss<br>(Title)                            |
|-----------------------------------------|------------|---------------------------------------------------------------|-------------------------------------------------|
| Approved:<br>OIL CONSERVATION COMMISSIO | DN         | I hereby certify that the info<br>to the best of my knowledge | ormation given above is true and complete<br>c. |
| L'a Those                               |            | Namedowin W                                                   | Wiseman                                         |
| (Namo)<br>Coras Inspector               |            | PositionForeman                                               | etroleum Corperation                            |
| (Title)                                 | (Date)     | Address Roswell S                                             | tar Route Tatum, New Mexico                     |



•

.