

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work is begun. This copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOTatum, New Mexico
(Place)September 1, 1953
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation Coleman W. Robinson "A" Well No. 3 in 0 (Unit)
(Company or Operator)

C/SW 1/4 SE 1/4 of Sec. 14, T. 11-S, R. 32-E, NMPM., Moore - Devonian Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

10,715' Total Depth. Lins. Finished drilling 7-7/8" hole @ 1:14 PM on 8/31/53.
Ran drill stem test from 10,700' to 10,715' - test was open 4 hours.
Recovered 1405' of water blanket and 2598' of salt and sulphur water.
No show of gas or oil. It is our intention to plug and abandon the above well. The following procedure will be effected. Spot a 35 sack cement plug from 10,601' to 10,715' - fill hole with heavy drilling mud and spot a 35 sack cement plug from 8300' to 8414' - fill hole with mud and spot a 35 sack cement plug from 3455' to 3572'. Will run casing cutter and attempt to cut and salvage 8-5/8" OD casing from approximately 1100'. Fill hole with mud and spot a 10 sack cement plug from 298' to 308' in bottom of 13-3/8" OD casing and a 10 sack cement plug for surface to 10' in top of 13-3/8" OD casing. A piece of 4" line pipe will be placed in top of 13-3/8" OD casing extending 5' above ground level to serve as a marker.

Approved SEP 4 1953, 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By J. Stanley
Title Engineer District

Amerada Petroleum Corporation
Company or Operator
By Irwin W. H. H. H. H. H.
Position Foreman
Send Communications regarding well to:

Name Amerada Petroleum Corporation
Address Roswell Star Route Tatum, New Mexico