

RECEIVED	
UTION	
ICE	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

AUG 27 11 43 AM '67

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name ALLIE LEE, ET AL
8. Farm or Lease Name ALLIE LEE
9. Well No. 1
10. Field and Pool, or Wildcat WILDCAT
12. County LEA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

☐ GAS WELL ☐ OTHER- RE-ENTRY

Operator  
L. McCLELLAN AND LEN MAYER  
of Operator  
O. Box 348, ROSWELL, NEW MEXICO 88201  
n of Well

LETTER 1, 1980 FEET FROM THE SOUTH LINE AND 660 FEET FROM  
EAST LINE, SECTION 23 TOWNSHIP 11-S RANGE 32-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

4336' G. L.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

1M REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
RARELY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER RE-ENTRY ATTEMPT <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

THIS WELL WAS RE-ENTERED JULY 29, 1967, SQUEEZED THE SLAUGHTER ZONE OF THE SAN ANDRES AND PERFORATED 4050, 4125, 4220'. ACIDIZED WITH 1000 GALS ACID. COMMUNICATED WITHIN THE PERFORATED ZONE. SQUEEZED WITH 125 SACKS. DRILLED CEMENT TO 4228'. RE-CEMENTED WITH 50 SACKS. PRESS. UP TO 2250#, HELD. DRILLED OUT CEMENT FROM 3850 TO 4225'. TESTED WITH PACKER TO 2500 PSI. HELD. PERF. 4198 - 4206', 4 SHOTS. ACIDIZED WITH 500 GALS. PERF. 4169, 65, 53, 51, 4095, 93, 85, 82, 79, 73, 71. ACIDIZED PERFS 4151-4169 WITH 1500 GALS. COMMUNICATED. SQUEEZED PERFS WITH 50 SACKS. DRILLED CEMENT FROM 3800 TO 4105. TESTED TO 1250, HELD. PERF. 4071, 73, 79, 82, 35, 91, 93, 95/1 SHOT PER FOOT. TREATED WITH 2000 GALS. ACID. SWABBED AND FLOWED 54 BARRELS LOAD. SWABBING 1 1/2 BARRELS PER HOUR. NO SHOW OF OIL.

PREP TO PLUG AND ABANDON.

*Prep to plug and abandon  
Vestak Aug 9, 1967 to Fred J. H.*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James L. McClellan TITLE OPERATOR DATE 8/23/67  
APPROVED BY [Signature] TITLE DATE  
CONDITIONS OF APPROVAL, IF ANY: