

7 PUBLIC

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

RECEIVED
JUN 22 1953
OIL CONSERVATION COMMISSION

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 19, 1953
(Date)

Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

Coleman W. Robinson
(Lease)

Noble Drilling Corporation
(Contractor)

Well No. 2 in the C/SE 1/4 NE 1/4 of Sec. 23

T. 11-S, R. 32-E, NMPM, Moore - Devonian Pool, Lea County.

The Dates of this work were as follows: June 18, 1953

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,671' Total Depth. Lime. Finished drilling 7-7/8" hole @ 5:45 AM on 6/14/53. Ran Schlumberger surveys. Ran a total of 300 jts of 5-1/2" OD casing set @ 10,658' and cemented with 600 sacks cement. Plug pumped down to 10,569' with max. pump pressure of 1600# at 2:15 PM on 6/14/53. Ran temperature survey - top of cement outside of 5-1/2" OD casing @ 768' or 72.45 ft. After WOG for 24 hours - test 5-1/2" OD casing before drilling cement with 1800# for 1/2 hour - no pressure drop. Drilled cement from 10,569' to 10,658' and washed to 10,671. Test 5-1/2" OD casing with 1800# for 1/2 hour after drilling cement - no pressure drop. Continued with completion operations

Witnessed by I. W. Wiseman
(Name)

Amerada Petroleum Corporation
(Company)

Foreman
(Title)

Approved: OIL CONSERVATION COMMISSION

Noy Yankrough
(Name)
District Inspector
JUN 22 1953
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Coleman W. Robinson

Position: Assistant District Superintendent

Representing: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mex.

Handwritten text at the top of the page, mostly illegible due to fading. Some words like "The" and "and" are visible.

Handwritten text in the middle section of the page, continuing the narrative or list.

Handwritten text in the lower middle section, appearing as a list or detailed notes.

Handwritten text at the bottom of the page, including a signature or date on the right side.