

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES Nov 5 10 30 AM '63

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)November 4, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation State **M "A"** Well No. **1** in **M**
(Company or Operator) (Unit)
SW $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **24**, T. **11S**, R. **32E**, NMPM., **Moore Devonian** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Dual completed in Wolfcamp gas and Devonian oil zones:

Plan To: Kill both zones with water. Pull both tubing strings. Mill out Baker Model "D" packer at 8240'. Set cast iron cement retainer at 10,446'. Squeeze 5-1/2" casing perforations from 10,450' to 10,500' with 150 sacks cement. Perforate 5-1/2" casing from 10,417' to 10,423' with 2 bullet shots per foot. Run 2-3/8" tubing, packer and holddown. Acidize the above perforations with 1000 gals. 15% regular acid, swab test. Kill well and pull tubing, packer and holddown. Run Baker Model "D" production packer on wireline and set at 8220'. Run combination string of 2-3/8" OD Non-upset and 2-1/16" OD tubing for Devonian zone set at 10,376'. Rerun 2-1/16" OD tubing for Wolfcamp zone. Swab both zones and resume production.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....Amerada Petroleum Corporation
Company or Operator

By.....

Position..... District Superintendent

Send Communications regarding well to:

Name..... Amerada Petroleum Corporation

Address..... Box 668 - Hobbs, New Mexico

Nov 2 10 30 AM '83
HOBBS OFFICE OF C. C.