

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off; result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 9, 1953  
(Date)Tatum, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation  
(Company or Operator)

State M<sup>th</sup>A<sup>th</sup>

(Lease)

Noble Drilling Corporation  
(Contractor)

Well No. 2 in the SE 1/4 SW 1/4 of Sec. 24

T. 11-S, R. 32-E, NMPM, Moore - Devonian Pool, Lea County.

The Dates of this work were as follows: April 9, 1953

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan ~~(was)~~ (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,630' Total Depth - Line. Finished drilling 7-7/8" hole @ 12:15 AM, 3/31/53. Ran Schlumberger surveys. Ran a total of 309 joints of 5-1/2" OD casing set @ 10,546 and cemented w/ 600 sacks cement. Pumped plug to 10,467' @ 2:25 PM, 4/1/53. Max. Pump pressure - 1700#. Ran temperature survey - top of cement outside of 5-1/2" casing @ 7716', or 68.7% fill. After WOC for 24 hours tested 5-1/2" casing with 1000# - no pressure drop. Drilled cement from 10,467' to 10,546' and washed open hole from 10,546' to 10,630'. Tested 5-1/2" OD casing with 1000# for 1/2 hour after drilling cement plug - no pressure drop. Continued with completion operations.

Witnessed by R. J. Brakey Amerada Petroleum Corporation Farm Boss  
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name R. J. BrakeyPosition Assistant District SuperintendentRepresenting Amerada Petroleum CorporationAddress Roswell Star Route Tatum, New Mexico

(Title)

(Date)

1600