

..Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 11336 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing: Dry Hole - Plugged & Abandoned March 14, 1953

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. 1515'	T. Devonian. 11,307'	T. Ojo Alamo.	
T. Salt. 1550'	T. Silurian.	T. Kirtland-Fruitland.	
B. Salt. 2163'	T. Montoya.	T. Farmington.	
T. Yates. 2292'	T. Simpson.	T. Pictured Cliffs.	
T. DEGL Artesia Red Sand 2993'	T. McKee.	T. Menefee.	
T. Queen.	T. Ellenburger.	T. Point Lookout.	
T. Grayburg.	T. Gr. Wash.	T. Mancos.	
T. San Andres 3570	T. Granite.	T. Dakota.	
T. Clear Paddock 5295'	T.	T. Morrison.	
T. Red Clearfork 5800'	T.	T. Penn.	
T. Tubbs. 6430'	T.	T.	
T. Abo. 7260'	T.	T.	
T. Penn. 8530'	T. Wolfcamp 8318'	T.	
T. Miss. 10720'	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	6'	6'	Cellar				
6'	1515'	1509'	Red Bed				
1515'	1550	35	Anhydrite				
1550'	2163	613	Salt Anhy & Shale				
2163'	2292	129	Shale Anhy				
2292'	2400	108'	Sand Shale & Anhy				
2400'	3570	1170	Salt Shale Anhy Sand				
3570'	6430	2860	Dolomite & Anhy				
6430'	7260	830	Dolomite Anhy, Sand				
7260'	8100	840	Shale, Dolomite, Anhy				
8100'	8315'	215	Dolomite & Anhy				
8315'	8450	135	Dolomite & Chert				
8450'	8610	160	Limestone, Dolomite, Chert				
8610'	9560	950	Limestone, Shale				
9560'	10610	1050	Simestone, Sand, Shale				
10610'	10720	110	Limestone & Shale				
10720'	11290	570	Limestone, Shale, Chert				
11290'	11305	15	Sand & Shale				
11305'	11336	31	Chert & Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 18, 1953 (Date)

Company or Operator: Amerada Petroleum Corporation Address: Roswell Star Route, Tatum, New Mexico

Name: K. V. Stephenson Position or Title: Assistant District Superintendent