

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOTatum, New Mexico
(Place)March 13, 1953
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation - State EGWB Well No. 2 in M
(Company or Operator) (Unit)
SW/ 1/4 SW/ 1/4 of Sec. 2, T. 12-S, R. 32-E, NMPM, East Caprock - Devonian Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

11,336' Total Depth. Line. Ran drill stem test from 11,326' to 11,336'.
Recovered 184' of drilling mud, lightly gas-cut and cut with
estimated 2% oil and 920' of black, odorous salt water.
Finished drilling 7-7/8" hole to 11,336' @ 3:23 AM, 3/12/53.
Ran Schlumberger surveys. It is our intention to plug and
abandon the above well. We will effect the following procedure:
Spot a 35 sack regular cement plug from 11,221' to 11,336';
spot a 65 sack regular cement plug from 8589' to 8600';
spot a 35 sack regular cement plug from 3498' to 3610';
spot a 10 sack regular cement plug in top of 8-5/8" OD
casing; (cement was circulated on 8-5/8" OD casing when
it was ran in well). Hole will be filled with heavy drilling
mud between cement plugs. A piece of 4" pipe will be
cemented in top of 8-5/8" and will extend 5' above ground level
to serve as a marker.

Approved.....
Except as follows:

Amerada Petroleum Corporation
By [Signature]
Position Assistant District Superintendent
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSIONBy Roy Guthrie
Title Assistant District Superintendent

Name Amerada Petroleum Corporation
Address Roswell Star Route Tatum, New Mexico