

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

JAN 20 1948

RECEIVED

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

January 18, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
**Amerada Petroleum Corporation** **State SCA** Well No. **1** in the \_\_\_\_\_  
 Company or Operator \_\_\_\_\_ Lease \_\_\_\_\_  
**SW<sub>1</sub> SE<sub>4</sub>** of Sec. **3**, T. **12S**, R. **32E**, N. M. P. M.,  
**Caprock** Field, **Lea** County.

The dates of this work were as follows: **January 16, 17, 1948**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **January 14,** 19 **48**  
 and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**3102' Total Depth, Anhydrite. Ran temperature survey and found top of cement at 1588', 35.4% of calculated fill. Nippled up 7" Casing, went in hole with 6 1/4" bit and drilled out cement from 3038' to 3102' to 11:25AM, 1-17-48. Tested casing with 800# for 30 minutes before and after drilling cement and OK. Started drilling 6 1/4" hole from 3102' at 4:05PM, 1-17-48.**

Witnessed by **Ray Seifert** **Amerada Petroleum Corporation** **Asst. Dist. Supt.**  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

**18th.** day of **January**, 19 **48**

Name **Ray Seifert**

Position **Asst. Dist. Supt.**

Representing **Amerada Petroleum Corporation**  
 Company or Operator

My commission expires \_\_\_\_\_

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

JAN 20 1948  
 Date \_\_\_\_\_

**Ray Seifert**  
 Name  
**OIL & GAS INSPECTOR**  
 Title